



US00D600311S

(12) **United States Design Patent**  
**Swan**

(10) **Patent No.:** **US D600,311 S**

(45) **Date of Patent:** **\*\* Sep. 15, 2009**

(54) **ACCESSORY MOUNT HAVING A BUFFER PAD**

(76) Inventor: **Richard E. Swan**, 171 West St., E. Bridgewater, MA (US) 02333

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/319,537**

(22) Filed: **Jun. 11, 2008**

(51) **LOC (9) Cl.** ..... **22-01**

(52) **U.S. Cl.** ..... **D22/109**

(58) **Field of Classification Search** ..... D22/100, D22/108, 109, 110, 199; 42/85, 90, 223, 42/124-128, 143, 71.01, 75.01; 89/37.03, 89/37.04

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

1,428,655	A	9/1922	Noske	
2,161,051	A	6/1939	Humeston	
3,877,166	A	4/1975	Ward	
4,845,871	A	7/1989	Swan	
4,860,480	A	8/1989	Ruger	
4,905,396	A	3/1990	Bechtel	
5,155,915	A	10/1992	Repa	
5,276,988	A	1/1994	Swan	
5,606,818	A	3/1997	Hardee	
5,669,173	A	9/1997	Rodney, Jr.	
5,680,725	A	10/1997	Bell	
6,442,883	B1	9/2002	Waterman et al.	
6,449,893	B2	9/2002	Spinner	
6,490,822	B1	12/2002	Swan	
6,513,276	B2	2/2003	Mendoza-Orozco	
6,598,333	B1	7/2003	Randazzo et al.	
D507,620	S *	7/2005	Swan	D22/109
6,922,934	B1	8/2005	Huan	
6,931,778	B1	8/2005	Nelson et al.	

D537,499	S *	2/2007	Swan	D22/110
D548,811	S *	8/2007	Swan	D22/109
7,272,904	B2	9/2007	Larue	
D555,750	S *	11/2007	Cheng	D22/109
D573,443	S *	7/2008	Swan	D8/343
2004/0148842	A1	8/2004	Aalto et al.	
2006/0123686	A1	6/2006	Larue	
2006/0207156	A1	9/2006	Larue	

**OTHER PUBLICATIONS**

Technical Manual, Operator, Organizational, Direct Support and General Support Maintenance Manual, "TM 9-4931-710-14&P", Headquarters, Department of the Army, Aug. 1986.

\* cited by examiner

*Primary Examiner*—Cathron C Brooks

*Assistant Examiner*—Melanie Levy

(74) *Attorney, Agent, or Firm*—Barlow, Josephs & Holmes, Ltd.

(57) **CLAIM**

The ornamental design for an accessory mount having a buffer pad, as shown and described.

**DESCRIPTION**

FIG. 1 is a perspective view of the accessory mount having a buffer pad in accordance with the present invention;

FIG. 2 is a top view thereof;

FIG. 3 is a bottom view thereof;

FIG. 4 is a right side view thereof;


FIG. 5 is a left side view thereof;


FIG. 6 is a rear end view thereof; and,

FIG. 7 is front end view thereof.


The features depicted in broken lines have been shown for illustrative purposes only and form no part of the claimed design.

**1 Claim, 5 Drawing Sheets**







**FIG. 1**




**FIG. 2**




**FIG. 3**




**FIG. 4**



**FIG. 5**



**FIG. 6**



**FIG. 7**