



US00D600697S

(12) **United States Design Patent**  
**Swiader**

(10) **Patent No.:** **US D600,697 S**

(45) **Date of Patent:** **\*\* Sep. 22, 2009**

(54) **DATA INPUT AND CURSOR CONTROL DEVICE**

(76) Inventor: **Michael C. Swiader**, 2 Jean St., Rye, NY (US) 10580

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/278,545**

(22) Filed: **Apr. 2, 2007**

**Related U.S. Application Data**

(62) Division of application No. 29/208,449, filed on Jun. 30, 2004, now Pat. No. Des. 541,805.

(51) **LOC (9) Cl.** ..... **14-02**

(52) **U.S. Cl.** ..... **D14/405**

(58) **Field of Classification Search** ..... D14/402–410, D14/412–417, 426, 427, 428, 430, 432, 435.1, D14/458; D13/168, 169; 345/156, 157, 345/158, 159, 160, 161, 162, 163, 164, 165, 345/166, 167; D15/18, 28, 17; 369/44.21, 369/44.23; 257/99

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,739,128	A	4/1988	Grisham	
4,795,296	A	1/1989	Jau	
4,862,165	A	8/1989	Gart	
4,994,795	A	2/1991	MacKenzie	
5,175,534	A	12/1992	Thatcher	
D340,479	S *	10/1993	HO	..... D14/416
5,296,871	A	3/1994	Paley	
D350,736	S	9/1994	Takahashi et al.	
5,355,147	A	10/1994	Lear	
D363,710	S	10/1995	Mateus et al.	
5,485,171	A	1/1996	Copper et al.	
D366,909	S *	2/1996	Hsieh	..... D14/412
D368,901	S *	4/1996	Currid	..... D14/417
5,512,892	A	4/1996	Corballis et al.	

D372,231	S	7/1996	Huang et al.	
D374,218	S *	10/1996	Sanchez et al.	..... D14/412
D381,701	S *	7/1997	Salinas	..... D14/416
5,648,798	A	7/1997	Hamling	
5,668,574	A	9/1997	Jarlance-Huang et al.	
5,698,784	A	12/1997	Hotelling et al.	
5,724,106	A	3/1998	Autry et al.	

(Continued)

*Primary Examiner*—Cathron C Brooks  
*Assistant Examiner*—Kevin K Rudzinski  
(74) *Attorney, Agent, or Firm*—Muncy, Geissler, Olds & Lowe, PLLC

(57) **CLAIM**

The ornamental design for a data input and cursor control device, as shown and described.

**DESCRIPTION**

FIG. 1 is a right side elevational view of a data input and cursor control device showing my new design;

FIG. 2 is a left side elevational view thereof;

FIG. 3 is a front elevational view thereof;

FIG. 4 is a rear elevational view thereof;

FIG. 5 is a top plan view thereof;

FIG. 6 is a bottom view thereof;

FIG. 7 is a right side elevational view of a date input and cursor control device showing my new design;

FIG. 8 is a left side elevational view thereof;

FIG. 9 is a front elevational view thereof;


FIG. 10 is a rear elevational view thereof;

FIG. 11 is a top plan view thereof; and,

FIG. 12 is a bottom view thereof.

The broken lines shown are included for the purpose of illustrating environmental structure and form no part of the claimed design.

**1 Claim, 10 Drawing Sheets**



# US D600,697 S

Page 2

---

## U.S. PATENT DOCUMENTS

5,767,841	A	6/1998	Hartman				
5,825,350	A	10/1998	Case, Jr. et al.				
5,898,421	A	4/1999	Quinn				
D413,880	S *	9/1999	Barnes et al.	.....	D14/416		
5,956,018	A *	9/1999	Pejic et al.	.....	345/157		
5,982,356	A *	11/1999	Akiyama	.....	345/161		
6,222,526	B1	4/2001	Holmes et al.				
6,281,883	B1	8/2001	Barker				
6,297,807	B1	10/2001	Eisbach et al.				
6,297,808	B1	10/2001	Yang et al.				
D458,261	S	6/2002	Tsai et al.				
D460,073	S *	7/2002	Whitehorn et al.	.....	D14/416		
D462,685	S *	9/2002	Yamamoto et al.	.....	D14/415		
D478,330	S *	8/2003	Yang	.....	D14/417		
D487,573	S *	3/2004	Yang	.....	D14/417		
6,816,151	B2 *	11/2004	Dellinger	.....	345/167		
6,892,481	B2 *	5/2005	Yamamoto et al.	.....	37/348		
D526,320	S *	8/2006	Brandon et al.	.....	D14/426		

\* cited by examiner




FIG. 1




FIG.2




FIG.3




FIG.4





FIG. 6




FIG. 7






FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12