

US00D601082S

(12) **United States Design Patent**
Cazin-Bourguignon et al.

(10) **Patent No.:** **US D601,082 S**
(45) **Date of Patent:** **** Sep. 29, 2009**

(54) **TIRE**

(75) Inventors: **Jean-Francois Cazin-Bourguignon**,
Audun-le-Tiche (FR); **Pascal**
Guillaume, Bastogne (BE);
Jean-Michel Alphonse Fernand
Gillard, Arlon (BE)

(73) Assignee: **The Goodyear Tire & Rubber**
Company, Akron, OH (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/333,942**

(22) Filed: **Mar. 18, 2009**

(51) **LOC (9) Cl.** **12-15**

(52) **U.S. Cl.** **D12/583**

(58) **Field of Classification Search** D12/544,
D12/548, 560–561, 566–567, 568, 579, 581–603,
D12/900–901; 152/209.1, 209.8–209.18,
152/209.25–209.28, 455

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D175,996 S	*	11/1955	Amspoker		D12/583
D265,184 S		6/1982	Hammond		D12/143
D269,002 S	*	5/1983	Hammond		D12/583
D269,003 S	*	5/1983	Hammond		D12/583
D288,914 S		3/1987	Hinkel et al.		D12/143
D289,025 S	*	3/1987	Stelzer		D12/548
D313,208 S	*	12/1990	Cottrell		D12/583
D348,238 S		6/1994	Ebbott		D12/141
D352,487 S		11/1994	Paulin et al.		D12/143
D367,447 S		2/1996	Hammond et al.		D12/143
D372,006 S	*	7/1996	Labbe		D12/583
D382,518 S	*	8/1997	Labbe et al.		D12/583
D382,519 S		8/1997	Young et al.		D12/143
D384,620 S		10/1997	Gillard et al.		D12/147
D388,030 S		12/1997	Schuster		D12/142
D388,031 S		12/1997	Loeffler et al.		D12/143
D390,511 S	*	2/1998	Rowe		D12/583
D391,533 S	*	3/1998	Labbe et al.		D12/583

D397,646 S	*	9/1998	Labbe et al.		D12/583
D402,236 S		12/1998	Harris et al.		D12/142
D402,237 S		12/1998	Harris et al.		D12/142
D402,238 S		12/1998	Young et al.		D12/142
D403,626 S		1/1999	Harris et al.		D12/142
D429,188 S	*	8/2000	Schuster et al.		D12/583
D458,582 S		6/2002	Rodicq et al.		D12/586
D496,329 S	*	9/2004	Thomas et al.		D12/583
D500,010 S		12/2004	Maziarka et al.		D12/590

* cited by examiner

Primary Examiner—Stacia Cadmus

(74) *Attorney, Agent, or Firm*—Richard B. O’Planick

(57) **CLAIM**

The ornamental design for a tire, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;

FIG. 2 is a front elevational view thereof;

FIG. 3 is a right side elevational view thereof; the opposite side elevational view being identical thereto;



FIG. 4 is an enlarged fragmentary front elevational view thereof;

FIG. 5 is a perspective view of a second embodiment of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread and that the opposite side perspective view is identical thereto; and,

FIG. 6 is a front elevational view of a second embodiment, it being understood that an enlarged fragmentary view thereof would be substantially identical to that shown in FIG. 4, with the exception of the inclusion of the sidewall in solid lines.

In the drawings, the broken lines showing of the sidewall, inner bead and the peripheral boundary between the tire tread and the sidewall in FIGS. 1 through 4 depict environmental subject matter and form no part of the claimed design.

1 Claim, 6 Drawing Sheets






FIG-1




FIG-2




FIG-3




FIG-4




FIG-5




FIG-6