



US00D602588S

(12) **United States Design Patent**
VanDenBogart et al.

(10) **Patent No.:** **US D602,588 S**

(45) **Date of Patent:** **** Oct. 20, 2009**

(54) **TAMPON APPLICATOR**

(75) Inventors: **Tom William VanDenBogart**, Slinger, WI (US); **Cao Hue Chi Pham**, Alpharetta, GA (US); **Yein Sze Ong**, Singapore (SG); **Franz Aschenbrenner**, Kastl (DE); **Dušan Pavlik**, Novy Jicin (CZ); **Gary Mastalish**, Oshkosh, WI (US); **Irina Tsareva**, Moscow Region (RU); **Lynn Ann Weggel**, Appleton, WI (US); **Anastasia Barlas**, Arncliffe (AU); **Priscilla Eng Choo Goh**, Maplewoods (SG); **EunJung Kang**, Seoul (KR)

(73) Assignee: **Kimberly-Clark Worldwide, Inc.**, Neenah, WI (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/321,369**

(22) Filed: **Jul. 15, 2008**

(51) **LOC (9) Cl.** **24-02**

(52) **U.S. Cl.** **D24/141**

(58) **Field of Classification Search** D24/141, D24/135; 604/14, 15, 11, 17, 902, 18, 16, 604/904, 385.17, 191, 206, 367, 363

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,042,040 A 7/1962 Galik

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0115193 2/1989

(Continued)

OTHER PUBLICATIONS

Moss, Mark D., Sequential Coinjection Hot Runner, Kona Corporation.

(Continued)

Primary Examiner—Ian Simmons

Assistant Examiner—Christopher Lee

(74) *Attorney, Agent, or Firm*—Armstrong Teasdale, LLP

(57) **CLAIM**

The ornamental design for a tampon applicator, as shown and described.

DESCRIPTION

FIG. 1 is a front elevation of a first embodiment of our new tampon applicator;

FIG. 2 is a rear elevation thereof, with a plunger of the tampon applicator shown in phantom and forming no part of the invention;

FIG. 3 is a right side elevation thereof;

FIG. 4 is a left side elevation thereof;

FIG. 5 is a top plan view thereof;

FIG. 6 is a bottom plan view thereof; and

FIG. 7 is a perspective view thereof;

FIG. 8 is a front elevation of a second embodiment of our new tampon applicator;

FIG. 9 is a rear elevation thereof, with a plunger of the tampon applicator shown in phantom and forming no part of the invention;

FIG. 10 is a right side elevation thereof;

FIG. 11 is a left side elevation thereof;



FIG. 12 is a top plan view thereof;

FIG. 13 is a bottom plan view thereof; and,

FIG. 14 is a perspective view thereof.

The broken lines of the plunger in the drawing figures are included for the purpose of illustrating an environmental that forms no part of the claimed design.

1 Claim, 14 Drawing Sheets



U.S. PATENT DOCUMENTS

3,765,417 A 10/1973 Crockford
 4,048,998 A 9/1977 Nigro
 D250,663 S 12/1978 Koch
 4,198,978 A 4/1980 Nigro
 4,361,150 A 11/1982 Voss
 4,447,222 A 5/1984 Sartinoranont
 4,536,178 A 8/1985 Lichstein
 4,620,534 A 11/1986 Zartman
 5,158,535 A 10/1992 Paul
 5,279,541 A 1/1994 Frayman
 5,389,067 A 2/1995 Rejai
 5,437,628 A 8/1995 Fox
 5,453,085 A 9/1995 Schoelling
 5,533,990 A * 7/1996 Yeo 604/363
 5,681,894 A 10/1997 Williams
 5,702,553 A 12/1997 Iskra
 5,709,652 A 1/1998 Hagerty
 5,746,710 A 5/1998 Nielson
 5,788,663 A 8/1998 Igaue
 5,788,664 A 8/1998 Scalise
 5,931,803 A 8/1999 Jackson
 D415,565 S 10/1999 Hayes
 6,095,999 A 8/2000 Jackson
 6,416,488 B1 7/2002 Jackson
 6,450,985 B1 9/2002 Schoelling
 6,450,986 B1 9/2002 Binner
 6,511,452 B1 1/2003 Rejai
 6,533,748 B2 3/2003 Buzot
 6,572,577 B1 6/2003 Binner
 6,610,025 B2 8/2003 Berg
 6,645,136 B1 11/2003 Zunker
 6,652,477 B2 11/2003 Karapasha
 6,673,032 B2 1/2004 Buzot
 6,695,763 B2 2/2004 Zunker
 D492,033 S * 6/2004 Jarmon et al. D24/141
 6,890,324 B1 5/2005 Jackson
 6,923,789 B2 8/2005 Lemay
 6,939,289 B2 9/2005 Zunker
 D515,212 S 2/2006 Edgett
 7,014,637 B1 3/2006 Denti
 7,044,928 B2 5/2006 Lemay

7,081,110 B2 7/2006 Karapasha
 7,172,573 B1 2/2007 Lamb
 7,241,274 B2 7/2007 Suga
 7,250,129 B2 7/2007 Williams
 D572,362 S * 7/2008 Edgett et al. D24/141
 2008/0004563 A1 1/2008 Lemay et al.
 2008/0033337 A1 2/2008 Dougherty

FOREIGN PATENT DOCUMENTS

EP 0392281 10/1990
 EP 1198215 8/2005
 EP 1551347 12/2007
 GB 2166656 5/1986
 WO 2001000126 1/2001
 WO 2007089306 8/2007
 WO 2008019093 2/2008

OTHER PUBLICATIONS

Selden, R., Sandwich Injection Molding of Thermoplastics—A Literature Survey, Journal of Injection Molding Technology, Dec. 1997, vol. 1, No. 4.
 Allan; Bevis; McCalla; Mubarak, Multi-Component Laminate Moulding, Wolfson Centre for Materials Processing, Brunel University, Uxbridge, U.K.
 Stewart, Richard, Multicomponent Molding: In-Mold Techniques Eliminate Downstream Operations To Cut Costs and Boost Quality, Plastics Engineering: North America Cover Story, www.4spe.org, Jun. 2008.
 Nguyen; Turcott; Derdouri; Ait Messaoud; Sanschagrín; Salamon; Koppi, Polymer Melt Flow Behavior in the Coinjection Molding Process, Industrial Materials Institute, National Council Canada; Ecole Polytechnique; Dow Chemical.
<http://www.businesswire.com/portal/site/exxonmobil/index>, ExxonMobil Chemical Introduces New Transparent and Translucent TPE Grades to Inspire Design, Jun. 10, 2008.
 Hartwig, Molding and Optimization of Barrier Properties for Stretch-blow Molded Bottles, Krupp Corpoplast Maschinenbau GmbH, D-22145 Hamburg, Germany, 5 pages.
 Selden, R., Coinjection Molding: Compatibilization of Polyamide-Polypropylene Sandwich Structures, Journal of Injection Molding Technology, Dec. 1998, vol. 2, No. 4, 10 pages, Molndal, Sweden.

* cited by examiner

FIG. 1




FIG. 2





FIG. 3






FIG. 4

FIG. 5





FIG. 6






FIG. 7

FIG. 8





FIG. 9






FIG. 10




FIG. 11

FIG. 12





FIG. 13






FIG. 14