



US00D606482S

(12) **United States Design Patent**
Lundgren et al.

(10) **Patent No.:** **US D606,482 S**

(45) **Date of Patent:** **** Dec. 22, 2009**

(54) **TIRE TREAD**

(75) Inventors: **Paula R. Lundgren**, Akron, OH (US);
Cory Williams, Medina, OH (US);
Richard Parr, Uniontown, OH (US)

(73) Assignee: **Bridgestone Americas Tire Operations, LLC**

(**) Term: **14 Years**

(21) Appl. No.: **29/337,036**

(22) Filed: **May 14, 2009**

(51) **LOC (9) Cl.** **12-15**

(52) **U.S. Cl.** **D12/532**

(58) **Field of Classification Search** D12/505-532,
D12/900-901; 152/209.1, 209.8-209.18,
152/209.25-209.28

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | |
|--------------|---------|------------------------|---------|
| 4,481,990 A | 11/1984 | Rieger et al. | |
| D335,478 S * | 5/1993 | Slingluff et al. | D12/531 |
| D409,959 S | 5/1999 | Maxwell | |
| D414,728 S * | 10/1999 | Gerresheim et al. | D12/532 |
| D451,451 S | 12/2001 | Smith | |
| D454,331 S | 3/2002 | Fierro et al. | |
| D455,119 S | 4/2002 | Welbes | |
| D456,343 S | 4/2002 | Allison | |
| D461,765 S | 8/2002 | Nonaka | |
| D475,344 S | 6/2003 | Tsubono | |
| D478,865 S | 8/2003 | Dixon et al. | |
| D480,351 S | 10/2003 | Dixon et al. | |
| D481,354 S | 10/2003 | Hutz et al. | |
| D482,321 S | 11/2003 | Hanna | |
| D484,845 S * | 1/2004 | Takahashi et al. | D12/531 |
| D485,232 S | 1/2004 | Nakamura | |
| D492,643 S | 7/2004 | Robert | |
| D497,143 S * | 10/2004 | Lee et al. | D12/532 |
| D500,733 S | 1/2005 | Himuro | |

| | | | |
|--------------|---------|---------------------|---------|
| D504,386 S * | 4/2005 | Seifert | D12/532 |
| D505,386 S | 5/2005 | Maxwell et al. | |
| D515,024 S | 2/2006 | Russell et al. | |
| D517,001 S | 3/2006 | Maziarka et al. | |
| D517,002 S | 3/2006 | Welbes | |
| D517,470 S | 3/2006 | Welbes | |
| D517,980 S | 3/2006 | Umstot et al. | |
| D538,221 S | 3/2007 | Losey et al. | |
| D544,431 S * | 6/2007 | Graas et al. | D12/532 |
| D545,264 S | 6/2007 | Takahashi et al. | |
| D549,155 S * | 8/2007 | Umstot et al. | D12/512 |
| D549,642 S | 8/2007 | Maxwell | |
| D574,316 S * | 8/2008 | Neidert et al. | D12/514 |
| D582,839 S * | 12/2008 | Lee et al. | D12/530 |

* cited by examiner

Primary Examiner—Stacia Cadmus

(74) *Attorney, Agent, or Firm*—Thomas R. Kingsbury

(57) **CLAIM**

The ornamental design for a tire tread, as shown and described.

DESCRIPTION

FIG. 1 is a side perspective view of a tire tread showing our new design, it being understood that the tread pattern is repeated throughout the circumference of the tire tread, the opposite side being the same as that shown;

FIG. 2 is a front elevational view thereof the opposite side being identical thereto;



FIG. 3 is a side elevational view of the right side thereof,

FIG. 4 is a side elevational view of the left side thereof; and,

FIG. 5 is an enlarged fragmentary front elevational view thereof.

The broken lines defining the tire sidewall, inner bead, and the peripheral boundary between the claimed tire tread and sidewall are for illustrative purposes only and form no part of the claimed design.

1 Claim, 5 Drawing Sheets






FIG-1




FIG-2




FIG-3




FIG-4




FIG-5