



US00D608273S

(12) **United States Design Patent**
Scheifele et al.

(10) **Patent No.:** **US D608,273 S**
(45) **Date of Patent:** **** Jan. 19, 2010**

(54) **TIRE SIDEWALL**

(75) Inventors: **Kevin E. Scheifele**, Atwater, OH (US);
Keith A. Dumigan, Akron, OH (US)

(73) Assignee: **Bridgestone Americas Tire Operations, LLC**

(**) Term: **14 Years**

(21) Appl. No.: **29/320,711**

(22) Filed: **Jul. 2, 2008**

(51) **LOC (9) Cl.** **12-15**

(52) **U.S. Cl.** **D12/605**

(58) **Field of Classification Search** D12/500–501,
D12/544, 579, 600, 605, 604; 152/523–524,
152/DIG. 12, 555; D7/588, 396.4–396.5

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D379,168 S	5/1997	Ratliff, Jr.
D380,718 S	7/1997	Ratliff, Jr.
5,645,661 A	7/1997	Clementz et al.
D385,834 S	11/1997	Ratliff, Jr.
D407,356 S	3/1999	Cross
D412,476 S	8/1999	Clementz et al.
D449,576 S	10/2001	Kajikawa
D450,034 S	11/2001	Kajikawa
D452,203 S	12/2001	Kajikawa
D457,130 S	5/2002	Ratliff, Jr. et al.
D479,190 S	9/2003	Maxwell
D480,047 S	9/2003	Kajikawa
D492,648 S	7/2004	Maxwell et al.
D500,013 S	12/2004	Maxwell et al.
D503,146 S	3/2005	Maxwell et al.
D506,435 S	6/2005	Maxwell et al.
D517,003 S	3/2006	Shondel
D540,250 S	4/2007	Shondel
D540,740 S	4/2007	Maxwell et al.
D541,210 S	4/2007	Maxwell et al.
D542,219 S	5/2007	Shondel et al.
D542,220 S	5/2007	Shondel et al.
D543,496 S	5/2007	Shondel et al.

D543,497 S	5/2007	Maxwell et al.
D543,932 S	5/2007	Shondel
D543,933 S	5/2007	Shondel
D544,831 S	6/2007	Kikkawa et al.
D547,261 S	7/2007	Shondel et al.
D549,167 S	8/2007	Iwabuchi
D550,151 S	9/2007	Maxwell
D552,536 S	10/2007	Shondel
D553,076 S	10/2007	Miyasaka
D557,202 S	12/2007	Shondel
D558,138 S	12/2007	Shondel
D561,089 S	2/2008	Maxwell
D563,310 S	3/2008	Shondel
D568,236 S	5/2008	Holden et al.

(Continued)

Primary Examiner—Stacia Cadmus

(74) *Attorney, Agent, or Firm*—Thomas R. Kingsbury

(57) **CLAIM**

The ornamental design for a tire sidewall, as shown and described.

DESCRIPTION

FIG. 1 is a side elevation view of a tire sidewall showing our design; and,



FIG. 2 is a side elevation view of a tire sidewall showing a second embodiment of our design; and,

FIG. 3 is a side elevation view of a tire sidewall showing a third embodiment of our design; and,

FIG. 4 is a side elevation view of a tire sidewall showing a fourth embodiment of our design.

The broken lines defining the tire, the brand name, and rotational direction indication are for illustrative purposes only and form no part of the claimed design.

1 Claim, 4 Drawing Sheets



US D608,273 S

Page 2

U.S. PATENT DOCUMENTS			
D569,338 S	5/2008	Shondel	
D569,792 S	5/2008	Holden et al.	
D569,793 S	5/2008	Dixon	
D570,768 S	6/2008	Takahashi	
D571,287 S	6/2008	Dixon	
D581,354 S *	11/2008	Harvey	D12/605 * cited by examiner
D588,529 S *	3/2009	Reese et al.	D12/605
D588,531 S *	3/2009	Maxwell	D12/605
D588,532 S *	3/2009	Shondel	D12/605
D593,487 S *	6/2009	Takahashi	D12/605
D596,119 S *	7/2009	Fujita	D12/605
D597,025 S *	7/2009	Fujita	D12/605
2002/0174928 A1	11/2002	Ratliff, Jr.	




FIG-1




FIG-2




FIG-3




FIG-4