



US00D608482S

(12) **United States Design Patent**
Brown et al.

(10) **Patent No.:** **US D608,482 S**
(45) **Date of Patent:** **** Jan. 19, 2010**

(54) **LIGHTING DEVICE**

(75) Inventors: **John R. Brown**, Mosman (AU); **Angelo Kotsis**, Marrickville (AU)

(73) Assignee: **Eveready Battery Company, Inc.**, St. Louis, MO (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/341,321**

(22) Filed: **Aug. 4, 2009**

(51) **LOC (9) Cl.** **26-02**

(52) **U.S. Cl.** **D26/49**

(58) **Field of Classification Search** D26/37,
D26/38, 39, 40, 46, 49, 50, 51, 56; 362/157,
362/158, 184, 186, 187, 194–196, 202, 204–206,
362/208, 253

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D449,395 S * 10/2001 Dalton et al. D26/49
D480,826 S * 10/2003 Englert et al. D26/49
D493,008 S * 7/2004 Brent D26/49
D494,298 S * 8/2004 Brent D26/49

D551,369 S * 9/2007 Mah D26/37
D600,841 S * 9/2009 Kung D26/46

* cited by examiner

Primary Examiner—Ian Simmons

Assistant Examiner—Carissa C Fitts

(74) *Attorney, Agent, or Firm*—Gregory J. Adams

(57) **CLAIM**

We claim the ornamental design for a lighting device, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of the lighting device.

FIG. 2 is a front view of the lighting device.

FIG. 3 is a rear view of the lighting device.


FIG. 4 is a right side view of the lighting device. The left side view is a mirror image of the right side view.

FIG. 5 is a top view of the lighting device; and,

FIG. 6 is a bottom view of the lighting device.

Any broken line(s) shown are for illustrative purposes only and form no part of the claimed design.

1 Claim, 2 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6