



US00D609346S

(12) **United States Design Patent**
Yu

(10) **Patent No.:** **US D609,346 S**
(45) **Date of Patent:** **** Feb. 2, 2010**

(54) **ELECTRIC SHOCK DEVICE**
(TWO-HOLES-HANDLES TYPED)

6,097,987 A * 8/2000 Milani 607/142
D460,556 S * 7/2002 Daynes et al. D24/168
D576,246 S * 9/2008 Pennington D22/117
D585,519 S * 1/2009 Pennington D22/117

(76) Inventor: **Kai Yu**, Room 602, No. 37, Lane 128,
Bei Liu Street, Jiang Dong District,
Zhejiang Province, Ning Bo City (CN)

* cited by examiner

Primary Examiner—T. Chase Nelson
Assistant Examiner—Anhdao Doan

(**) Term: **14 Years**

(21) Appl. No.: **29/334,272**

(57) **CLAIM**

(22) Filed: **Mar. 24, 2009**

The ornamental design for an electric shock device (two-holes-handle typed), as shown and described.

(30) **Foreign Application Priority Data**

Nov. 27, 2008 (CN) 2008 3 0285931

DESCRIPTION

(51) **LOC (9) Cl.** **24-02**

FIG. 1 is the front view of an electric shock device (two-holes handle typed) showing my new design;

(52) **U.S. Cl.** **D24/168; D22/117**

FIG. 2 is the rear view thereof;

(58) **Field of Classification Search** D24/164–169,
D24/186; 607/4–7, 142, 145, 149, 150; D22/117,
D22/199; 361/232; 42/1.08

FIG. 3 is the top view thereof;

See application file for complete search history.

FIG. 4 is the bottom view thereof;

FIG. 5 is the left view thereof;

FIG. 6 is the right view thereof; and,

FIG. 7 is the perspective view thereof.


The broken lines in FIGS. 2 and 4 are included for the purpose of illustrating portions of the electric shock device that form no part of the claimed design.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,196,877 A * 7/1965 Corbin 607/142
D244,153 S * 4/1977 Jones D24/168
D256,504 S * 8/1980 Davis D24/168
D257,391 S * 10/1980 Gammon D24/168

1 Claim, 4 Drawing Sheets






FIG.1




FIG.2




FIG.3




FIG.4




FIG.5




FIG.6




FIG.7