



US00D612814S

(12) **United States Design Patent**
Nishikawa

(10) **Patent No.:** **US D612,814 S**
(45) **Date of Patent:** **** Mar. 30, 2010**

(54) **CONTROLLER FOR HANDPIECE**

(75) Inventor: **Hirotohi Nishikawa**, Saitama-ken (JP)

(73) Assignee: **Urawa Kohgyo Co., Ltd.**, Kuki-Shi (JP)

(**) Term: **14 Years**

(21) Appl. No.: **29/293,296**

(22) Filed: **Nov. 15, 2007**

(51) **LOC (9) Cl.** **14-03**

(52) **U.S. Cl.** **D13/168**

(58) **Field of Classification Search** D13/168;
D10/104, 106; D14/218, 247; 340/825.22,
340/825.24, 825.25, 825.31, 825.36, 825.69,
340/825.72; 341/76; 455/352

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D253,234 S *	10/1979	Cooke	D13/168
D255,564 S *	6/1980	Brooksby et al.	D13/168
D306,998 S *	4/1990	Mintz et al.	D13/164
D363,673 S *	10/1995	Dziersk et al.	D10/104
D428,856 S	8/2000	Fujimaki		
D429,220 S	8/2000	Fujimaki		
D453,743 S	2/2002	Ono		
D464,030 S	10/2002	Fujimaki		
6,494,830 B1 *	12/2002	Wessel	600/300

FOREIGN PATENT DOCUMENTS

JP	D0875918	8/1993
JP	D1103332	1/2001

* cited by examiner

Primary Examiner—Selina Sikder

(74) *Attorney, Agent, or Firm*—Jordan and Hamburg LLP

(57) **CLAIM**

The ornamental design for the controller for handpiece, as shown and described.

DESCRIPTION

FIG. 1 is a front elevational view of my new design;

FIG. 2 is a rear elevational view thereof;

FIG. 3 is a right side elevational view thereof shown at a larger scale for ease of illustration;

FIG. 4 is a left side elevational view thereof shown at a larger scale for ease of illustration; the broken lines are shown for illustrative purposes only and form no part of the claimed design;

FIG. 5 is a top plan view thereof;

FIG. 6 is a bottom plan view thereof;


FIG. 7 is a top plan view thereof indicating cross-sectional reference lines A-C and B-B';

FIG. 8 is a front elevational view thereof of a cross section taken along line A-B-B'-C; and,

FIG. 9 is front top right side perspective view thereof.

The controller for a handpiece is a controller for controlling a handpiece that is used for nail treatment, tereotics, jewelry work, die machining, medical use, dental use and other precision machining. The controller for a handpiece is used to connect a handpiece plug to a connection terminal shown as a small circular cutout at a lower right side of the right side elevational view, and shown as a small circular cutout in a lower right of the reference perspective view. In a connected state, upon turning on a power switch shown as a circular shape at a left side of the right side elevational view, and as a circular shape outwardly protruding in the reference perspective view, a handpiece bit is caused to operate, thereby enabling cutting, grinding, piecing and other precision machining. Further, upon turning an adjustment knob cylindrically protruding and shown at a about a center of the right side elevational view and at a lower right side of the reference perspective view, a motor rotation speed is changed, thereby achieving bit operation suitable for precision machining.

1 Claim, 9 Drawing Sheets






FIG. 1





FIG. 2

FIG. 3






FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9