

#### (12) United States Design Patent US D613,947 S (10) Patent No.: **\*\*** Apr. 20, 2010 Gibbons et al. (45) **Date of Patent:**

- PURSE WITH REMOVABLE SWATCHES (54)
- (75)Inventors: **Yvette Delores Gibbons**, Austell, GA (US); James Calvin Perry, Austell, GA (US)
- Assignee: **Yvette D. Gibbons (Perry)**, Austell, GA (73)(US)

14 Years (\*\*` l'erm:

*Primary Examiner*—Holly H Baynham

(57)CLAIM

The ornamental design for a purse with removable swatches, as shown and described.

### DESCRIPTION

FIG. 1 is a front elevational view of the purse with removable

Appl. No.: 29/310,481 (21)

#### Aug. 21, 2008 (22)Filed:

- LOC (9) Cl. ..... 03-01 (51)
- (52)
- Field of Classification Search ...... D3/232–234, (58)D3/240, 252; 150/100, 103–104, 106–110, 150/113–114, 118–119

See application file for complete search history.

(56)**References** Cited

#### U.S. PATENT DOCUMENTS

2,436,579 A *	2/1948	Kritchman 150/10	4
2,522,549 A *	9/1950	Waggoner 150/10	4
2,656,870 A *	10/1953	Wishnia 150/10	4
3,575,226 A *	4/1971	Chapman 150/10	4

\* cited by examiner

swatches

FIG. 2 is a front elevational view with one of the swatches inserted; and,

FIG. 3 is another front elevational view with a different swatch inserted.

My purse design is characterized by the unique cut out front design to display the multiple colors of swatches that can be inserted inside of the purse. Creating a coordinated look with the carriers' ensemble without having to change purses.

The purse has a unique design cut out of the front through the fabric making the design visible inside the purse. Inside the front of the purse is a pocket covering the cut out design. In this pocket, swatches of different colors made of the same fabric as the outside of the purse can be inserted. These swatches can be interchangeable to match the carriers' ensemble.

### 1 Claim, 3 Drawing Sheets









# **U.S. Patent** Apr. 20, 2010 Sheet 1 of 3 US D613,947 S



















## U.S. Patent Apr. 20, 2010 Sheet 2 of 3 US D613,947 S













*Fig. 2* 

## U.S. Patent Apr. 20, 2010 Sheet 3 of 3 US D613,947 S







-







