



US00D615028S

(12) **United States Design Patent**
Kajita et al.

(10) **Patent No.:** **US D615,028 S**
(45) **Date of Patent:** **** May 4, 2010**

(54) **TIRE FOR AUTOMOBILE**

D604,692 S * 11/2009 Ebiko et al. D12/587
D605,108 S * 12/2009 Brown et al. D12/588

(75) Inventors: **Hiroaki Kajita**, Hyogo (JP); **Hiroyuki Kurosawa**, Hyogo-ken (JP)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **The Goodyear Tire & Rubber Company**, Akron, OH (US)

JP 1178533 7/2003

(**) Term: **14 Years**

* cited by examiner

(21) Appl. No.: **29/322,727**

Primary Examiner—Caron Veynar
Assistant Examiner—Katrina A Kile

(22) Filed: **Aug. 11, 2008**

(74) *Attorney, Agent, or Firm*—Richard B. O'Planick

(30) **Foreign Application Priority Data**

Mar. 10, 2008 (JP) 2008-005856

(57) **CLAIM**

The ornamental design for a tire for automobile, as shown and described.

(51) **LOC (9) Cl.** **12-15**

(52) **U.S. Cl.** **D12/586**

(58) **Field of Classification Search** D12/503,
D12/505, 533, 534, 535, 536, 537, 543, 547,
D12/548, 549, 550, 564, 565, 566, 567, 568,
D12/569–572, 579, 583–588, 594, 595, 596,
D12/597, 598, 599, 600–604; 152/209.1,
152/209.8, 209.9, 209.18, 209.25, 209.28
See application file for complete search history.

DESCRIPTION

FIG. 1 is a perspective view of a tire for automobile showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;

FIG. 2 is a front elevational view thereof;

FIG. 3 is a right side elevational view thereof; the opposite side elevational view being identical thereto;

FIG. 4 is an enlarged fragmentary front elevational view thereof;

FIG. 5 is a perspective view of a second embodiment of a tire for automobile showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread and that the opposite side perspective view is identical thereto; and,

FIG. 6 is a front elevational view of a second embodiment, it being understood that an enlarged fragmentary view thereof would be substantially identical to that shown in FIG. 4, with the exception of the inclusion of the sidewall in solid lines.


In the drawings the broken lines defining the sidewall, inner bead and the peripheral boundary between the tire tread and the sidewall in FIGS. 1 through 4 are for illustrative purposes only and form no part of the claimed design.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D313,210 S 12/1990 Tsutsumi et al. D12/146
D316,693 S 5/1991 Kawabata et al. D12/147
D352,489 S 11/1994 Breny et al. D12/147
D515,019 S 2/2006 Umstot et al. D12/519
D535,939 S * 1/2007 Gordon et al. D12/583
D536,663 S 2/2007 Heinen et al. D12/603
D549,161 S * 8/2007 Morrison et al. D12/579
D555,080 S * 11/2007 Radulescu D12/587
D581,351 S * 11/2008 Morrison et al. D12/588
D584,681 S * 1/2009 Shimada D12/602
D585,364 S * 1/2009 Shondel et al. D12/600
D590,331 S * 4/2009 Miyazaki D12/584
D601,949 S * 10/2009 Shinkai D12/585
D602,425 S * 10/2009 Guspodin et al. D12/602

1 Claim, 6 Drawing Sheets






FIG-1




FIG-2




FIG-3




FIG-4



FIG-5




FIG-6