



US00D616127S

(12) **United States Design Patent**
Taiga

(10) **Patent No.:** **US D616,127 S**

(45) **Date of Patent:** **** May 18, 2010**

(54) **COMBINED CONNECTOR AND ILLUMINATION DEVICE**

(75) Inventor: **Keiji Taiga**, Tokyo (JP)

(73) Assignee: **Crops Co., Ltd.**, Tokyo (JP)

(**) Term: **14 Years**

(21) Appl. No.: **29/347,131**

(22) Filed: **Sep. 29, 2009**

(30) **Foreign Application Priority Data**

Sep. 4, 2009 (TW) 98304201

(51) **LOC (9) Cl.** **26-05**

(52) **U.S. Cl.** **D26/60; D26/67**

(58) **Field of Classification Search** D26/28,
D26/37, 44, 60, 61, 63, 67, 72, 80; 362/191,
362/196, 197, 200, 396, 397, 431, 473-476
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- D90,858 S * 10/1933 Rowe D26/60
- D121,016 S * 6/1940 Mitchell D26/60
- D127,212 S * 5/1941 Warsaw D26/60
- D130,339 S * 11/1941 Mitchell D26/60
- D267,747 S * 1/1983 Sassmannshausen D26/28
- D267,748 S * 1/1983 Sassmannshausen D26/28
- D302,325 S * 7/1989 Charet et al. D26/60
- 5,353,008 A * 10/1994 Eikenberry et al. 340/479
- D428,171 S * 7/2000 Schultz D26/28
- D438,653 S * 3/2001 Ljungstrom D26/28
- D524,974 S * 7/2006 Zernov D26/60

D609,377 S * 2/2010 Taiga D26/60
2003/0128547 A1 * 7/2003 Shoji 362/475

* cited by examiner

Primary Examiner—Clare E Heflin

(74) *Attorney, Agent, or Firm*—Rosenberg, Klein & Lee

(57) **CLAIM**

The ornamental design for a combined connector and illumination device, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view, taken from the front, top, and left side of a combined connector and illumination device showing my new design;

FIG. 2 is a front elevational view thereof;

FIG. 3 is a rear elevational view thereof;

FIG. 4 is a right side elevational view thereof;

FIG. 5 is a left side elevational view thereof;


FIG. 6 is a top plan view thereof;

FIG. 7 is a bottom plan view thereof;

FIG. 8 is a perspective view to show that the combined connector and illumination device of my new design is connected to a post and the illumination device is positioned upward at an angle, the broken line showing the post that is not claimed; and,

FIG. 9 is a perspective view to show that the combined connector and illumination device of my new design is connected to a post and the illumination device is positioned downward at an angle, the broken line showing the post that is not claimed.

1 Claim, 9 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9