



US00D616972S

(12) **United States Design Patent**  
**Wang**

(10) **Patent No.:** **US D616,972 S**  
(45) **Date of Patent:** **\*\* Jun. 1, 2010**

(54) **BURNER WITH STABLIZERS**

(75) Inventor: **Jianping Wang**, Jiangsu (CN)

(73) Assignee: **Changzhou Gardensun Furnace Co., Ltd.**, Changzhou, Jiangsu (CN)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/309,895**

(22) Filed: **Nov. 6, 2008**

(51) **LOC (9) Cl.** ..... **23-03**

(52) **U.S. Cl.** ..... **D23/332; D23/317; D23/314**

(58) **Field of Classification Search** ..... D23/323,  
D23/328, 332, 336, 339, 342, 386, 338;  
126/25 R, 67, 92 A, 92 B, 9 A; 362/92, 217,  
362/253; 431/331, 344


See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,922,158 A 7/1999 Culp et al.  
5,964,233 A 10/1999 Clark et al.  
6,057,012 A 5/2000 Culp et al.  
6,076,546 A 6/2000 Waters  
D429,324 S 8/2000 Olson et al.  
6,102,031 A 8/2000 Waters  
6,164,273 A 12/2000 Waters  
6,192,878 B1 2/2001 Waters  
D445,889 S 7/2001 Resmo et al.  
D446,290 S \* 8/2001 Jeng ..... D23/328  
D447,796 S 9/2001 Resmo et al.  
D450,816 S 11/2001 Bilotti  
D451,988 S \* 12/2001 Ashton et al. .... D23/328  
D455,204 S \* 4/2002 Bossler ..... D23/342  
D456,498 S \* 4/2002 Jeng ..... D23/328  
6,397,835 B1 \* 6/2002 Liang ..... 126/92 B  
D461,548 S \* 8/2002 Hsieh ..... D23/342  
D462,426 S \* 9/2002 Jeng ..... D23/328  
D462,427 S \* 9/2002 Jeng ..... D23/328  
6,446,623 B1 9/2002 Resmo et al.  
6,470,877 B1 10/2002 Waters  
D466,993 S 12/2002 Chang  
D471,622 S 3/2003 Bossler

D471,967 S 3/2003 Bossler  
D472,623 S 4/2003 Bossler  
6,550,470 B2 \* 4/2003 Liang ..... 126/92 B  
D474,532 S 5/2003 Chan et al.  
6,598,990 B2 7/2003 Li  
6,619,281 B2 9/2003 Resmo et al.  
6,650,830 B2 11/2003 Kerec  
6,651,647 B2 11/2003 Waters  
6,668,818 B2 12/2003 Bossler  
D486,211 S 2/2004 Chan et al.  
D486,567 S 2/2004 Sakai  
6,736,132 B2 5/2004 Schlosser et al.  
6,742,814 B2 6/2004 Resmo et al.  
6,745,759 B2 6/2004 Bossler  
6,792,937 B2 9/2004 Resmo et al.  
6,907,875 B1 6/2005 Eastman, II et al.  
D509,291 S 9/2005 Cunningham et al.  
7,003,217 B2 2/2006 Bachinski et al.  
7,086,396 B2 8/2006 Waters  
D532,500 S 11/2006 Yeung  
D532,501 S 11/2006 Giovino  
7,175,424 B2 2/2007 Frink et al.  
7,278,418 B2 10/2007 Duphily et al.  
7,296,522 B1 11/2007 Mahmalji  
D590,201 S \* 4/2009 Zagar ..... D7/335  
2001/0037804 A1 11/2001 Waters et al.  
2002/0088454 A1 7/2002 Resmo et al.  
2002/0089178 A1 7/2002 Resmo et al.  
2003/0029438 A1 2/2003 Bossler  
2003/0029439 A1 2/2003 Bossler  
2003/0056782 A1 \* 3/2003 Liang ..... 126/92 B  
2003/0056783 A1 3/2003 Bossler  
2003/0067765 A1 4/2003 Li  
2003/0099468 A1 5/2003 Kerec  
2003/0136396 A1 7/2003 Resmo et al.  
2004/0011346 A1 1/2004 Sakai  
2004/0226551 A1 11/2004 Duphily et al.  
2004/0261780 A1 12/2004 Frink et al.  
2005/0105898 A1 5/2005 Bachinski et al.  
2005/0175950 A1 8/2005 Waters  
2005/0247074 A1 11/2005 Ellicott  
2006/0198084 A1 9/2006 Hall, Jr. et al.  
2007/0101983 A1 5/2007 Yao  
2007/0267399 A1 11/2007 Flores  
2007/0269758 A1 11/2007 Hofbauer et al.  
2008/0006263 A1 1/2008 Seichei et al.





2008/0152329 A1 6/2008 Saunders et al.

## FOREIGN PATENT DOCUMENTS

WO	WO 00/08965	2/2000
WO	WO 00/17580	3/2000
WO	WO 01/45854	6/2001
WO	WO 02/24019	3/2002
WO	WO 02/073092	9/2002
WO	WO 2004/023954	3/2004
WO	WO 2004/082376	9/2004
WO	WO 2004/099674	11/2004
WO	PCT/GB05/000177	4/2005
WO	WO 2005/071321	8/2005
WO	WO 2005/072209	8/2005
WO	WO 2006/017003	2/2006
WO	WO 2006/024916	3/2006
WO	WO 2007/001364	1/2007

\* cited by examiner

*Primary Examiner*—T. Chase Nelson*Assistant Examiner*—Ania K Dworzecka(74) *Attorney, Agent, or Firm*—Lau & Associates, LLC

## (57) CLAIM

The ornamental design for a burner with stabilizers, as shown and described.

## DESCRIPTION

Embodiment 1 - FIGS. 1–7, 9 and 28–30.

Embodiment 2 - FIGS. 1–6, 8–9 and 28–30.

Embodiment 3 - FIGS. 8–15 and 28–30.

Embodiment 4 - FIGS. 8–9, 16–21 and 28–30.

Embodiment 5 - FIGS. 8–9, 22–27 and 28–30.

FIG. 1 is a perspective view of a first embodiment of a burner with a push-up switch and a door which opens in a counter-clock-wise direction and the door is in the close position and an adjustable table is set in a high position;

FIG. 2 is a perspective view of a burner with a push-up switch and a door which opens in a counter-clock-wise direction and the door is in the open position and an adjustable table is set in a high position;

FIG. 3 is a front plan view of a burner with a push-up switch and a door which open in a counter-clock-wise direction and an adjustable table is set in a high position;

FIG. 4 is one side plan view of a burner with a push-up switch and a door which opens in a counter-clock-wise direction and an adjustable table is set in a high position;

FIG. 5 is another side plan view of a burner with a push-up switch and a door which opens in a counter-clock-wise direction and an adjustable table is set in a high position;

FIG. 6 is a rear plan view of a burner with a push-up switch and a door which opens in a counter-clock-wise direction and an adjustable table is set in a high position;

FIG. 7 is a top plan view of a multi-piece top cover of a burner; FIG. 8 is an alternative second embodiment top plan view of a unibody top cover of a burner;

FIG. 9 is a bottom plan view of a burner showing the underside of the burner base and partial impeded view of the underside of the top cover;

FIG. 10 is a perspective view of a third embodiment of a burner with a push-up switch and a door which opens in a

clock-wise direction and the door is in the close position and an adjustable table is set in a high position;

FIG. 11 is a perspective view of a burner with a push-up switch and a door which opens in a clock-wise direction and the door is in the open position and an adjustable table is set in a high position;

FIG. 12 is a front plan view of a burner with a push-up switch and a door which open in a clock-wise direction and an adjustable table is set in a high position;

FIG. 13 is one side plan view of a burner with a push-up switch and a door which opens in a clock-wise direction and an adjustable table is set in a high position;

FIG. 14 is another side plan view of a push-up switch and a burner with a door which opens in a clock-wise direction and an adjustable table is set in a high position;

FIG. 15 is a rear plan view of a burner with a push-up switch and a door which opens in a clock-wise direction and an adjustable table is set in a high position;

FIG. 16 is a perspective view of a fourth embodiment of a burner with a push-in switch in the same plane as the temperature control switch and a door in a closed position which opens in a counter-clock-wise direction and an adjustable table is set in a low position;

FIG. 17 is a perspective view of a burner with a push-in switch in the same plane as the temperature control switch and a door in an open position which opens in a counter-clock-wise direction and an adjustable table is set in a low position;

FIG. 18 is a front view of a burner with a push-in switch in the same plane as the temperature control switch and a door opens in a counter-clock-wise direction and an adjustable table is set in a low position;

FIG. 19 is one side view of a burner with a push-in switch in the same plane as the temperature control switch and a door opens in a counter-clock-wise direction and an adjustable table is set in a low position;

FIG. 20 is another side view of a burner with a push-in switch in the same plane as the temperature control switch and a door opens in a counter-clock-wise direction and an adjustable table is set in a low position;

FIG. 21 is a rear view of a burner with a push-in switch in the same plane as the temperature control switch and a door opens in a counter-clock-wise direction and an adjustable table is set in a low position;

FIG. 22 is a perspective view of a fifth embodiment of a burner with a push-in switch in the same plane as the temperature control switch and a door in a closed position which opens in a clock-wise direction and an adjustable table is set in a low position;

FIG. 23 is a perspective view of a burner with a push-in switch in the same plane as the temperature control switch and a door in an open position which opens in a clock-wise direction and an adjustable table is set in a low position;

FIG. 24 is a front view of a burner with a push-in switch in the same plane as the temperature control switch and a door opens in a clock-wise direction and an adjustable table is set in a low position;

FIG. 25 is one side view of a burner with a push-in switch in the same plane as the temperature control switch and a door opens in a clock-wise direction and an adjustable table is set in a low position;

FIG. **26** is another side view of a burner with a push-in switch in the same plane as the temperature control switch and a door opens in a clock-wise direction and an adjustable table is set in a low position;

FIG. **27** is a rear view of a burner with a push-in switch in the same plane as the temperature control switch and a door opens in a clock-wise direction and an adjustable table is set in a low position;

FIG. **28** is an enlarged perspective view of the latch in all embodiments;

FIG. **29** is an enlarged side view of the latch in all embodiments; and,

FIG. **30** is an enlarged front view of the latch in all embodiments.

**1 Claim, 27 Drawing Sheets**




FIG.1




FIG.2






FIG.3




FIG. 4




FIG. 5






FIG.6




FIG. 7




FIG. 8




FIG. 9




FIG.10






FIG. 11




FIG.12




FIG.13




FIG.14






FIG.15




FIG.16




FIG.17




FIG.18






FIG. 19




FIG. 20




FIG.21




FIG.22






FIG.23




FIG.24




FIG. 25




FIG. 26




FIG.27






FIG. 28




FIG. 29




FIG. 30