



US00D619456S

(12) **United States Design Patent**  
**Walters**

(10) **Patent No.:** **US D619,456 S**  
(45) **Date of Patent:** **\*\* Jul. 13, 2010**

(54) **LID FOR TUMBLER OR JAR**

D603,704 S \* 11/2009 Jost et al. .... D9/449

(75) Inventor: **Cliff R. Walters**, Canal Winchester, OH  
(US)

\* cited by examiner

*Primary Examiner*—Susan Bennett Hattan

(73) Assignee: **Lynd Enterprises, Ltd.**, Lithopolis, OH  
(US)

(74) *Attorney, Agent, or Firm*—Frank H. Foster; Kremblas & Foster

(\*\*) Term: **14 Years**

(57) **CLAIM**

(21) Appl. No.: **29/336,832**

The ornamental design for a lid for tumbler or jar, as shown and described.

(22) Filed: **May 11, 2009**

**DESCRIPTION**

(51) **LOC (9) Cl.** ..... **09-07**

FIG. 1 is a perspective view of a lid for tumbler or jar showing my new design.

(52) **U.S. Cl.** ..... **D9/454; D9/444**

FIG. 2 is top, plan view thereof.

(58) **Field of Classification Search** ..... D9/529,  
D9/521, 454, 452, 447, 445, 435, 530, 453,  
D9/724, 448, 538, 438; 220/200, 806, 716,  
220/258.2, 257.1; 215/200, 261, 260; 222/520,  
222/521, 212

FIG. 3 is a side elevation view thereof. The lid design is axially symmetrical and side elevation views from all directions are identical to FIG. 3.

See application file for complete search history.

FIG. 4 is a bottom view thereof.

(56) **References Cited**

FIG. 5 is a view in section, taken along the line 5—5 of FIG. 4, revealing a side view of the interior thereof including circumferentially spaced legs spaced radially inwardly from the periphery of the lid. All of the circumferentially spaced legs are identically configured; and,

**U.S. PATENT DOCUMENTS**

- D320,554 S \* 10/1991 Van Dine et al. .... D9/574
- 5,346,088 A \* 9/1994 Brimo, II ..... 220/806
- D371,485 S \* 7/1996 Hickey ..... D7/392.1
- D445,337 S \* 7/2001 Croft et al. .... D9/504
- 6,360,909 B1 \* 3/2002 Bridge ..... 220/258.2
- D512,914 S \* 12/2005 Moretti ..... D9/454
- D536,614 S \* 2/2007 Peterson et al. .... D9/454

FIG. 6 is a view in section, taken along the line 6—6 of FIG. 4, revealing a side view of a circumferentially spaced leg viewed from radially outwardly of the upstanding leg.

**1 Claim, 3 Drawing Sheets**




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5





Fig. 6