



US00D619586S

(12) **United States Design Patent**
Richter

(10) **Patent No.:** **US D619,586 S**
(45) **Date of Patent:** **** Jul. 13, 2010**

(54) **APPARATUS HOLDER SUPPORT DEVICE**

(76) Inventor: **Harald Richter**, Höhenstrasse 32, 75331
Engelsbrand (DE)

(**) Term: **14 Years**

(21) Appl. No.: **29/315,996**

(22) Filed: **Aug. 14, 2009**

(51) **LOC (9) Cl.** **08-07**

(52) **U.S. Cl.** **D14/447; D14/253**

(58) **Field of Classification Search** D14/447,
D14/451, 452, 432, 439, 448, 457, 203.8,
D14/217, 224, 224.1, 238.1, 239, 251, 252,
D14/253, 371, 372, 373, 374, 375, 376, 377,
D14/378, 379, 381, 382, 434, 126; D6/310,
D6/311, 312, 313, 314, 406.3, 406.4, 406.5,
D6/406.6, 419, 420; D8/383, 373, 380; D12/415;
379/454, 455; 312/223.3; 248/917, 918,
248/919, 920, 921, 922, 923, 924, 447.2,
248/455, 460, 228.6, 276.1, 281.11; 361/679.02,
361/679.04, 679.06, 679.07, 679.09, 679.21,
361/679.26, 679.27, 679.3, 679.55, 679.56
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | | |
|--------------|---------|----------------|-------|---------|
| D337,333 S * | 7/1993 | Turk | | D14/251 |
| D521,850 S * | 5/2006 | Richter et al. | | D8/354 |
| D545,825 S * | 7/2007 | Richter | | D14/447 |
| D545,826 S * | 7/2007 | Richter | | D14/447 |
| D567,810 S * | 4/2008 | Yeh | | D14/253 |
| D579,854 S * | 11/2008 | Mo | | D12/415 |
| D587,188 S * | 2/2009 | Mo | | D12/415 |
| D588,903 S * | 3/2009 | Carnevali | | D8/355 |
| D591,755 S * | 5/2009 | Richter | | D14/447 |
| D593,103 S * | 5/2009 | Richter | | D14/447 |

| | | | | |
|--------------|---------|---------|-------|---------|
| D599,355 S * | 9/2009 | Richter | | D14/447 |
| D602,024 S * | 10/2009 | Richter | | D14/447 |
| D602,025 S * | 10/2009 | Richter | | D14/447 |

* cited by examiner

Primary Examiner—Jennifer Rivard

Assistant Examiner—Angela J Lee

(74) *Attorney, Agent, or Firm*—Klaus J. Bach

(57) **CLAIM**

The ornamental design for an apparatus holder support device, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of an apparatus holder support device;

FIG. 2 is a front side view of the apparatus holder support device shown in FIG. 1,

FIG. 3 is a bottom view of the apparatus holder support device shown in FIG. 2,

FIG. 4 is a left end view of the apparatus holder support device shown in FIG. 2,


FIG. 5 is a right end view of the apparatus holder support device shown in FIG. 2,


FIG. 6 is a rear side view of the apparatus holder support device shown in FIG. 2, and,

FIG. 7 is a top view of the apparatus holder support device shown in FIG. 2.

The apparatus holder support device is used for supporting an apparatus support device specifically adapted to cradling a particular apparatus such as a wireless phone, GPS, a PDA device, a telephone or other equipment in a convenient position on a smooth surface such as a windshield of a motor vehicle.

1 Claim, 6 Drawing Sheets








FIG. 2




FIG. 3




FIG. 5




FIG. 4




FIG. 6




FIG. 7