



US00D620634S

(12) **United States Design Patent**  
**Komar et al.**

(10) **Patent No.:** **US D620,634 S**  
(45) **Date of Patent:** **\*\* Jul. 27, 2010**

(54) **LUMINAIRE ASSEMBLY**

(75) Inventors: **Jürgen Komar**, Rott Am Inn (DE);  
**Florian Wildner**, Munich (DE)  
(73) Assignee: **OSRAM Gesellschaft mit  
beschränkter Haftung**, Munich (DE)  
(\*\*) Term: **14 Years**  
(21) Appl. No.: **29/341,984**  
(22) Filed: **Aug. 17, 2009**  
(30) **Foreign Application Priority Data**

Feb. 18, 2009 (EM) ..... 001097646

(51) **LOC (9) Cl.** ..... **26-03**  
(52) **U.S. Cl.** ..... **D26/93**  
(58) **Field of Classification Search** ..... D26/1,  
D26/24, 63, 67, 93-94, 104-110; 362/3,  
362/153, 186, 217, 225, 235, 25, 257, 277,  
362/317, 351, 353, 362, 363, 382, 431, 433,  
362/458

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

D280,025	S	*	8/1985	Waters	.....	D26/24
5,001,614	A	*	3/1991	Buss	.....	362/225
D317,364	S	*	6/1991	Cross	.....	D26/93
D370,072	S	*	5/1996	Arden	.....	D26/93
D374,737	S	*	10/1996	Can	.....	D26/80
D477,093	S	*	7/2003	Moriyama et al.	.....	D26/3
6,682,205	B2	*	1/2004	Lin	.....	362/235
D513,082	S	*	12/2005	Hoshikawa et al.	.....	D26/1
D531,139	S	*	10/2006	Egawa et al.	.....	D26/93
D536,110	S	*	1/2007	Wright	.....	D26/24
D573,730	S	*	7/2008	Uemoto et al.	.....	D26/24
D581,571	S	*	11/2008	Levine	.....	D26/63
D594,588	S	*	6/2009	Fanning	.....	D26/93

\* cited by examiner

*Primary Examiner*—Brian N Vinson

(57) **CLAIM**

The ornamental design for a luminaire assembly, as shown and described.

**DESCRIPTION**

FIG. 1 is a perspective front right side view of the luminaire and the fixture of the luminaire assembly;

FIG. 2 is a front view thereof;

FIG. 3 is a right side view thereof;

FIG. 4 is a back view thereof;

FIG. 5 is a top view thereof;

FIG. 6 is a left side view thereof;

FIG. 7 is a bottom view thereof;

FIG. 8 is a perspective front right side view of the luminaire assembly in which the luminaire is clamped in the fixture;

FIG. 9 is a front view thereof;

FIG. 10 is a right side view thereof;

FIG. 11 is a back view thereof;

FIG. 12 is a left side view thereof;

FIG. 13 is a top view thereof;

FIG. 14 is a bottom view thereof;

FIG. 15 is a perspective front right side view of the luminaire assembly in which the luminaire is clamped in the fixture in an alternative position;

FIG. 16 is a perspective front right side view of the luminaire assembly in which the luminaire is clamped in the fixture in a second alternative position;

FIG. 17 is a front view of the luminaire assembly in which the luminaire is clamped in the fixture according to the position shown in FIG. 15;

FIG. 18 is a left side view thereof;

FIG. 19 is a back view thereof;

FIG. 20 is a top view thereof; and,

FIG. 21 is a bottom view thereof.

In an embodiment, the luminaire assembly includes a portable, cylindrical luminaire having four LEDs and a fixture for mounting the luminaire in a vertical or horizontal position. The fixture can be mounted to a seat by screws, by a magnet or by an adherend.

**1 Claim, 21 Drawing Sheets**




FIG 1




FIG 2




FIG 3




FIG 4




FIG 5




FIG 6




FIG 7






FIG 8




FIG 9




FIG 10




FIG 11




FIG 12




FIG 13




FIG 14




FIG 15






FIG 16




FIG 17




FIG 18



FIG 19




FIG 20




FIG 21

