



US00D621539S

(12) **United States Design Patent**
McAtamney et al.

(10) **Patent No.:** **US D621,539 S**

(45) **Date of Patent:** **** Aug. 10, 2010**

(54) **EXAMINATION LIGHT**

(75) Inventors: **Michael McAtamney**, Navan (IE);
Stephen Montgomery, Lucan (IE);
Michael Krynock, Sunnyvale, CA (US);
Morten Wagener, Copenhagen (DK)

(73) Assignee: **Welch Allyn, Inc.**, Skaneateles Falls, NY
(US)

(**) Term: **14 Years**

(21) Appl. No.: **29/344,529**

(22) Filed: **Sep. 30, 2009**

(51) **LOC (9) Cl.** **26-05**

(52) **U.S. Cl.** **D26/61**

(58) **Field of Classification Search** D26/61-66,
D26/24, 72, 51; 362/220, 297, 282, 296.03,
362/402, 400, 804, 294, 345, 347, 371, 399,
362/98; 600/249; 433/29, 215

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | | |
|---------------|---------|-----------------|-------|------------|
| D201,038 S * | 5/1965 | Sullivan et al. | | D26/61 |
| 3,191,023 A * | 6/1965 | Jones et al. | | 362/220 |
| D217,497 S * | 5/1970 | Valeska | | D26/61 |
| 4,234,247 A * | 11/1980 | Dorman | | 362/297 |
| 4,254,454 A * | 3/1981 | Hardin, Jr. | | 362/282 |
| 4,254,455 A * | 3/1981 | Neal, Jr. | | 362/296.03 |
| 4,494,177 A * | 1/1985 | Matthews | | 362/402 |
| D286,082 S * | 10/1986 | Shwisha | | D26/61 |
| D301,627 S * | 6/1989 | Sestak | | D26/24 |
| D308,112 S * | 5/1990 | Targetti | | D26/72 |
| 4,930,058 A * | 5/1990 | Jones et al. | | 362/400 |

| | | | | |
|----------------|--------|------------------|-------|--------|
| D348,742 S * | 7/1994 | Rorke et al. | | D26/51 |
| D377,227 S * | 1/1997 | Nordstrom et al. | | D26/65 |
| D463,056 S * | 9/2002 | Waites | | D26/65 |
| 6,733,290 B2 * | 5/2004 | West et al. | | 433/29 |
| D523,984 S * | 6/2006 | Cai | | D26/61 |
| 7,163,306 B1 * | 1/2007 | Major et al. | | 362/98 |
| D563,011 S * | 2/2008 | Major | | D26/61 |
| D586,026 S * | 2/2009 | Hanson et al. | | D26/61 |

* cited by examiner

Primary Examiner—Mitchell I Siegel

(57) **CLAIM**

The ornamental design for an examination light, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of an examination light according to an embodiment of the present invention;

FIG. 2 is a bottom view of the examination light shown in FIG. 1;

FIG. 3 is a top view of the examination light shown in FIG. 1;

FIG. 4 is a right side view of the examination light shown in FIG. 1;


FIG. 5 is a left side view of the examination light shown in FIG. 1;

FIG. 6 is a front view of the examination light shown in FIG. 1; and,

FIG. 7 is a rear view of the examination light shown in FIG. 1.

The broken lines shown herein are for illustrative purposes only and form no part of the claimed design.

1 Claim, 4 Drawing Sheets






FIG. 1

FIG. 2





FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7