



US00D622799S

(12) **United States Design Patent**  
**Cameron**

(10) **Patent No.:** **US D622,799 S**

(45) **Date of Patent:** **\*\* Aug. 31, 2010**

(54) **BALL MARKER**

(75) Inventor: **Don T. Cameron**, Carlsbad, CA (US)

(73) Assignee: **Acushnet Company**, Fairhaven, MA (US)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/319,300**

(22) Filed: **Jun. 6, 2008**

**Related U.S. Application Data**

(63) Continuation of application No. 12/134,399, filed on Jun. 6, 2008.

(51) **LOC (9) Cl.** ..... **21-02**

(52) **U.S. Cl.** ..... **D21/794**

(58) **Field of Classification Search** ..... D21/793-794;  
473/286, 406

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

2,107,944	A	2/1938	Howard	
D169,125	S *	3/1953	Cheresh	D21/467
3,041,071	A	6/1962	Fialon	
3,850,434	A *	11/1974	Ockenfels	273/274
4,521,018	A *	6/1985	Cotchonis	473/406
5,356,133	A *	10/1994	Bellagamba	473/406
5,437,446	A	8/1995	Youngkin	
5,476,258	A	12/1995	Frisone	
D405,858	S *	2/1999	Wolff	D21/759
D428,954	S *	8/2000	Tate	D21/793
D462,102	S *	8/2002	Urbik	D21/794

6,739,980	B2	5/2004	Scott et al.	
D533,460	S *	12/2006	Terrasi	D9/600
D583,893	S *	12/2008	Ruff	D21/794
2005/0026727	A1	2/2005	Barouh	

**OTHER PUBLICATIONS**

“Using Your Ball Marker,” [www.vbsa.org.au/Referees](http://www.vbsa.org.au/Referees), 2 pages, Jun. 3, 2008.

“Tools of the Trade,” [www.prosnookerref.co.uk/tools\\_of\\_the\\_trade.php](http://www.prosnookerref.co.uk/tools_of_the_trade.php), 2 pages, 2006.

“Image Gallery,” [www.prosnookerref.co.uk/images.php](http://www.prosnookerref.co.uk/images.php), 3 pages, 2006.

“Putting Tools” from Golf by Colors, [www.puttingtool.com/live/](http://www.puttingtool.com/live/), 2 pages, Apr. 30, 2009.

\* cited by examiner

*Primary Examiner*—Mitchell I Siegel

(74) *Attorney, Agent, or Firm*—Kristin D. Wheeler

(57) **CLAIM**


The ornamental design for a ball marker, as shown and described.

**DESCRIPTION**

FIG. 1 is a perspective view of my new design for a top surface of a ball marker comprising a flat top surface with one side forming an arcuate perimeter portion having an edge with a slight radius as shown, the remaining sides forming a rectangular shaped perimeter and also having an edge with a radius as shown, a plurality of first indicia and a plurality of relatively smaller second indicia provided adjacent the arcuate perimeter portion; and,

FIG. 2 is a top view of the embodiment of FIG. 1.

**1 Claim, 1 Drawing Sheet**






FIG. 1




FIG. 2