



US00D625726S

(12) **United States Design Patent**
Crisp et al.

(10) **Patent No.:** **US D625,726 S**
(45) **Date of Patent:** **** Oct. 19, 2010**

(54) **COORDINATE INPUT DEVICE**

(75) Inventors: **Thomas Crisp**, Beaverton, OR (US);
Michael Keith Lemmon, Portland, OR
(US); **Pierre Harper**, Portland, OR
(US); **Kai Halsinger**, Portland, OR (US)

(73) Assignee: **Wacom Co., Ltd.**, Saitama (JP)

(**) Term: **14 Years**

(21) Appl. No.: **29/344,456**

(22) Filed: **Sep. 29, 2009**

(30) **Foreign Application Priority Data**

Apr. 28, 2009 (JP) 2009-009785

(51) **LOC (9) Cl.** **14-02**

(52) **U.S. Cl.** **D14/389**

(58) **Field of Classification Search** D14/388–390,
D14/341, 342, 383, 384, 374, 381, 356;
D19/52; D10/61, 63, 65; 178/18.01, 18.03–18.11;
345/173–178

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D308,055 S *	5/1990	Tedham et al.	D14/389
D308,198 S *	5/1990	Tedham et al.	D14/389
D333,125 S *	2/1993	Komada et al.	D14/390
D359,984 S *	7/1995	Mak	D14/390
D366,037 S *	1/1996	Kawauchi et al.	D14/389
D377,169 S *	1/1997	Chida	D14/389
D377,789 S *	2/1997	Wang et al.	D14/390
D378,211 S *	2/1997	Kuo	D14/390
D390,211 S *	2/1998	Yates et al.	D14/390
D398,593 S *	9/1998	Tominaga et al.	D14/339
D501,473 S *	2/2005	Nakata	D14/341
D504,889 S *	5/2005	Andre et al.	D14/341
D519,997 S *	5/2006	Hirota	D14/341
D524,308 S *	7/2006	Lai	D14/346
D525,621 S *	7/2006	Hirota	D14/346
D554,640 S *	11/2007	Ponnert et al.	D14/388
D563,806 S *	3/2008	Jeon	D10/65

D574,272 S *	8/2008	Stevens et al.	D10/65
D586,812 S *	2/2009	Guenther	D14/383
D589,961 S *	4/2009	Hackenberg et al.	D14/389
D602,022 S *	10/2009	Heck et al.	D14/389
D602,488 S *	10/2009	Jiang et al.	D14/341

(Continued)

FOREIGN PATENT DOCUMENTS

JP D1314721 11/2007

Primary Examiner—Cathron C Brooks
Assistant Examiner—Deanna Fluegeman
(74) *Attorney, Agent, or Firm*—Seed IP Law Group PLLC


(57) **CLAIM**

The ornamental design for a coordinate input device, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a coordinate input device showing a new design;
FIG. 2 is a front elevational view of the coordinate input device;
FIG. 3 is a back elevational view of the coordinate input device;
FIG. 4 is a top plan view of the coordinate input device;
FIG. 5 is a bottom view of the coordinate input device;
FIG. 6 is a right side elevational view of the coordinate input device; and,
FIG. 7 is a left side elevational view of the coordinate input device.

1 Claim, 5 Drawing Sheets



US D625,726 S

Page 2

U.S. PATENT DOCUMENTS

D608,781 S *	1/2010	Wada	D14/371	D617,792 S *	6/2010	Andre et al.	D14/341
D613,286 S *	4/2010	Lee et al.	D14/341	2010/0116560 A1*	5/2010	Sato	178/18.01
							* cited by examiner




Fig.1.



Fig.2.



Fig.3.




Fig.4.




Fig. 5.



Fig. 6.




Fig. 7.