



US00D626445S

(12) **United States Design Patent**  
**Déhon**

(10) **Patent No.:** **US D626,445 S**

(45) **Date of Patent:** **\*\* Nov. 2, 2010**

(54) **ESCAPEMENT SPRING FOR A  
CLOCKWORK-MOVEMENT**

(75) Inventor: **Nicolas Déhon**, La Chaux-de-Fonds  
(CH)

(73) Assignee: **Sowind S.A.**, La Chaux-de Fonds (CH)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/324,540**

(22) Filed: **Sep. 15, 2008**

(30) **Foreign Application Priority Data**

Mar. 25, 2008 (WO) ..... DM/069 914

(51) **LOC (9) Cl.** ..... **10-07**

(52) **U.S. Cl.** ..... **D10/129**

(58) **Field of Classification Search** ..... D10/128,  
D10/129, 30-39; 368/124-133, 168-178  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,973	A *	2/1841	Crane	.....	422/102
31,999	A *	4/1861	Reed	.....	368/133
D2,189	S *	10/1865	Hubbell	.....	D10/129
303,058	A *	8/1884	Scott	.....	368/101
318,208	A *	5/1885	Sandmark	.....	368/173
512,328	A *	1/1894	Saati	.....	368/76
1,022,987	A *	4/1912	Vincent	.....	368/150
1,423,410	A *	7/1922	Fawver	.....	368/138
2,108,776	A *	2/1938	Mcnicoll	.....	368/169
2,354,020	A *	7/1944	Honger	.....	368/124
2,642,714	A *	6/1953	Contant et al.	.....	368/164
2,845,772	A *	8/1958	Beyner	.....	368/127
2,924,728	A *	2/1960	Biemiller	.....	310/27
2,936,571	A *	5/1960	Biemiller	.....	368/170

2,954,663	A *	10/1960	Biemiller et al.	.....	368/162
3,058,292	A *	10/1962	Reese	.....	368/169
3,262,260	A *	7/1966	Perrot-Audet	.....	368/170
3,416,304	A *	12/1968	Little	.....	368/184
D336,865	S *	6/1993	Besson	.....	D10/129
D339,751	S *	9/1993	Besson	.....	D10/39
D438,473	S *	3/2001	Dumas	.....	D10/39
6,520,674	B1 *	2/2003	Tokoro	.....	368/127
6,863,434	B2 *	3/2005	Mojon	.....	368/127
D505,342	S *	5/2005	Hayek	.....	D10/39
D530,628	S *	10/2006	Raffy	.....	D10/32
D568,180	S *	5/2008	Laucella	.....	D10/39
7,473,027	B2 *	1/2009	Goeller	.....	368/124

\* cited by examiner

*Primary Examiner*—Lucy Lieberman

(74) *Attorney, Agent, or Firm*—Sughrue Mion, PLLC

(57) **CLAIM**

The ornamental design for a escapement spring for a clockwork-movement, as shown and described.

**DESCRIPTION**

FIG. 1 is a front view of my new escapement spring for a clockwork-movement in a first working position;

FIG. 2 is a front view thereof in a second working position;

FIG. 3 is a top view thereof;

FIG. 4 is a right side view thereof;

FIG. 5 is a front perspective view of the escapement spring for a clockwork-movement shown in an alternate position;


FIG. 6 is a left side view thereof;

FIG. 7 is front elevation of FIG. 5;

FIG. 8 is a bottom view thereof; and,

FIG. 9 is a rear elevation of FIG. 5.

**1 Claim, 9 Drawing Sheets**






FIG. 1




FIG. 2



FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7






FIG. 8




FIG. 9