



US00D626451S

(12) **United States Design Patent**
Helwig et al.

(10) **Patent No.:** **US D626,451 S**

(45) **Date of Patent:** **** Nov. 2, 2010**

(54) **FASTENER COMPONENT**

D489,292 S * 5/2004 Matsui et al. D11/220
D493,388 S * 7/2004 Candotti D11/226
D516,953 S * 3/2006 Hollingworth et al. D11/220

(75) Inventors: **Rodney H. Helwig**, Lexington, KY
(US); **Chuck G. Lecompte**, Frankfort,
KY (US); **Chad A. Clark**,
Lawrenceburg, KY (US)

FOREIGN PATENT DOCUMENTS

| | | |
|----|---------|---------|
| DE | 1807760 | 9/1970 |
| DE | 2035735 | 4/1972 |
| JP | 405391 | 10/1950 |
| JP | 5190644 | 8/1976 |
| JP | 637695 | 10/1994 |
| JP | 73924 | 2/1995 |
| JP | 3084098 | 12/2001 |

(73) Assignee: **YKK Corporation of America**,
Marietta, GA (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/347,097**

* cited by examiner

(22) Filed: **Sep. 18, 2009**

Primary Examiner—T. Chase Nelson

Assistant Examiner—Mark Cavanna

(51) **LOC (9) Cl.** **02-07**

(74) *Attorney, Agent, or Firm*—Kilpatrick Stockton, LLP

(52) **U.S. Cl.** **D11/220**

(58) **Field of Classification Search** D11/200,
D11/220; D8/382; 24/113 R, 113 MP, 114.9,
24/303, 662–681, 623, 682.1, 693–695
See application file for complete search history.

(57) **CLAIM**

The ornamental design for a fastener component, as shown and described.

(56) **References Cited**

DESCRIPTION

U.S. PATENT DOCUMENTS

| | | | | |
|-----------|-----|---------|-----------------|---------|
| 1,562,190 | A | 11/1925 | Reiter | |
| 4,805,272 | A * | 2/1989 | Yamaguchi | 24/623 |
| 4,805,273 | A * | 2/1989 | Burke et al. | 24/662 |
| D301,567 | S * | 6/1989 | Burke | D11/220 |
| D350,501 | S * | 9/1994 | Schriever | D11/220 |
| 5,441,095 | A | 8/1995 | Trethewey | |
| 5,797,643 | A | 8/1998 | Demedash | |
| D410,412 | S * | 6/1999 | Tominaga et al. | D11/220 |
| D466,439 | S * | 12/2002 | Wagner et al. | D11/220 |
| D473,158 | S * | 4/2003 | Matsui et al. | D11/220 |
| D473,820 | S * | 4/2003 | Ming | D11/220 |
| D477,246 | S * | 7/2003 | Takeda | D11/220 |
| D481,654 | S * | 11/2003 | Matsui et al. | D11/220 |

FIG. 1 is a perspective view of a fastener component, showing our new design;

FIG. 2 is a side elevation view thereof;

FIG. 3 is another side elevation view thereof;


FIG. 4 is another side elevation view thereof;

FIG. 5 is another side elevation view thereof; and,

FIG. 6 is a top view thereof.

In the drawings, the broken lines form no part of the claimed design.

1 Claim, 3 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6