



US00D626500S

(12) **United States Design Patent**  
**Fujita**

(10) **Patent No.:** **US D626,500 S**

(45) **Date of Patent:** **\*\* Nov. 2, 2010**

(54) **TIRE FOR AUTOMOBILE**

(75) Inventor: **Masayuki Fujita**, Kyoto-fu (JP)

(73) Assignee: **The Goodyear Tire & Rubber Company**, Akron, OH (US)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/363,898**

(22) Filed: **Jun. 16, 2010**

(30) **Foreign Application Priority Data**

Dec. 18, 2009 (JP) ..... 2009-030594

(51) **LOC (9) Cl.** ..... **12-15**

(52) **U.S. Cl.** ..... **D12/561; D12/544**

(58) **Field of Classification Search** ..... D12/533–567,  
D12/602, 900–901, 571, 579, 596; 152/209.1,  
152/209.8–209.19, 209.25–209.28

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

D158,031 S	4/1950	Wilcox	.....	D90/20
D265,187 S	6/1982	Raluy	.....	D12/149
D284,364 S	6/1986	Nakamishi et al.	.....	D12/147
D284,650 S *	7/1986	Mader	.....	D12/544
D287,236 S	12/1986	Yonekura et al.	.....	D12/140
D291,875 S *	9/1987	Hayakawa et al.	.....	D12/544
D302,261 S	7/1989	Kato	.....	D12/151
D307,120 S *	4/1990	Ingley et al.	.....	D12/561
D312,063 S *	11/1990	Covert et al.	.....	D12/566
D316,385 S *	4/1991	Marriott	.....	D12/561
D316,533 S *	4/1991	Killian	.....	D12/567
D340,897 S	11/1993	Kurada	.....	D12/147
D366,232 S	1/1996	Ueda	.....	D12/146
D381,301 S *	7/1997	Lo	.....	D12/567
D381,943 S *	8/1997	Ueda	.....	D12/561
D382,839 S *	8/1997	Labbe et al.	.....	D12/561
D396,675 S *	8/1998	Johenning et al.	.....	D12/566
D429,191 S *	8/2000	Baker	.....	D12/561
D430,515 S *	9/2000	Baker	.....	D12/561
D436,063 S *	1/2001	Baker	.....	D12/561

D448,708 S 10/2001 Shinoda et al. .... D12/147

D452,960 S 1/2002 Shinoda et al. .... D12/147

D464,613 S \* 10/2002 Weaver ..... D12/544

(Continued)

*Primary Examiner*—Stacia Cadmus

(74) *Attorney, Agent, or Firm*—Richard B. O’Planick

(57) **CLAIM**

The ornamental design for a tire for automobile, as shown and described.

**DESCRIPTION**

FIG. 1 is a perspective view of a tire for automobile showing my new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;

FIG. 2 is a front elevational view thereof;

FIG. 3 is a right side elevational view thereof; the other side being a mirror image thereof;



FIG. 4 is an enlarged fragmentary front elevational view thereof;

FIG. 5 is a perspective view of a second embodiment of a tire for automobile showing my new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread and that the opposite side view is a mirror image thereof; and,

FIG. 6 is a front elevational view of a second embodiment, it being understood that an enlarged fragmentary view thereof would be substantially identical to that shown in FIG. 4, with the exception of the inclusion of the sidewall in solid lines.

In the drawings, the broken lines showing of the sidewall, inner bead and the peripheral boundary between the tire tread and the sidewall in FIGS. 1 through 4 depict environmental subject matter and form no part of the claimed design.

**1 Claim, 6 Drawing Sheets**



# US D626,500 S

Page 2

---

## U.S. PATENT DOCUMENTS

D471,151 S	3/2003	Otsuji .....	D12/559	D525,190 S	7/2006	Oohigashi .....	D12/544
D505,382 S *	5/2005	Green et al. ....	D12/544	D527,703 S	9/2006	Oohigashi .....	D12/579
D522,961 S *	6/2006	Kuramochi et al. ....	D12/544	D530,262 S	10/2006	Chapman et al. ....	D12/543
				D555,079 S *	11/2007	Lee .....	D12/561

\* cited by examiner




FIG-1




FIG-2




FIG-3




FIG-4




FIG-5




FIG-6