

(12) United States Design Patent

Elmer et al.

(10) Patent No.:

US D627,632 S

(45) Date of Patent:

** Nov. 23, 2010

(54) LOCKING MECHANISM FOR SECURING CORDS, HOSES OR CABLES

(76) Inventors: Warren Elmer, 1383 Coast Meridian

Road, Port Coquitlam, BC (CA) V3C 6L1; **Malcolm Kehr**, 179 Bracewell Drive, Penticton, BC (CA) V2A 6X1

(**) Term: 14 Years

(21) Appl. No.: 29/345,362

(22) Filed: Oct. 14, 2009

(30) Foreign Application Priority Data

Ap	or. 17, 2009 (CA)	. 130424
(51)	LOC (9) Cl	08-08
(52)	U.S. Cl	D8/383
(58)	Field of Classification Search	D8/330,
	D8/331, 333, 383; 70/14, 19,	202, 203
	See application file for complete search history	ory.

(56) References Cited

U.S. PATENT DOCUMENTS

1,197,020	A	*	9/1916	Farrar 70/203
3,667,259	\mathbf{A}	*	6/1972	Reque et al 70/14
5,167,135	\mathbf{A}	*	12/1992	Gobeski 70/14
D334,883	S	*	4/1993	Fraker et al D8/369
D477,768	S	*	7/2003	Bridges et al D8/333
6,997,420	B2	,	2/2006	Yudis et al.
D587,988	S	*	3/2009	Johansson
D613,137	S	*	4/2010	Wieberdink et al D8/14

^{*} cited by examiner

Primary Examiner—Holly H Baynham
Assistant Examiner—Sheryl Lane

(74) Attorney, Agent, or Firm—Procopio, Cory, Hargreaves & Savitch LLP

(57) CLAIM

The ornamental design for a locking mechanism for securing cords, hoses or cables, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a locking mechanism for securing cords, hoses or cables in a closed position, showing my new design;

FIG. 2 is a front view thereof;

FIG. 3 is a rear view thereof;

FIG. 4 is a left side elevation view thereof;

FIG. **5** is a right side elevation view thereof;

FIG. 6 is a bottom view thereof;

FIG. 7 is a top view thereof;

FIG. 8 is a perspective view thereof, illustrating the locking mechanism for securing cords, hoses or cables in an open position;

FIG. 9 is a perspective view of a second embodiment of the locking mechanism for securing cords, hoses and cables shown in FIG. 1.

FIG. 10 is a front view of the locking mechanism for securing cords, hoses or cables in the closed position;

FIG. 11 is a rear view of the locking mechanism for securing cords, hoses or cables in the closed position;

FIG. 12 is a left side elevation view of the locking mechanism for securing cords, hoses or cables in the closed position;


FIG. 13 is a right side elevation view of the locking mechanism for securing cords, hoses or cables in the closed position;

FIG. 14 is a bottom view of the locking mechanism for securing cords, hoses or cables in the closed position;

FIG. 15 is a top view of the locking mechanism for securing cords, hoses or cables in the closed position; and,

FIG. 16 is a perspective view of the locking mechanism for securing cords, hoses or cables in an open position.

1 Claim, 12 Drawing Sheets








FIGURE 1




FRARE 2



PGIRE 3









FROME 6




HAURE 7




FRURE 8




HAURE 9



FRURE 10



AGUNE 11




FRURE 12






FIGURE 13



FBIFE 14



FIGURE 15



FRUIRE 16