



US00D627632S

(12) **United States Design Patent**
Elmer et al.

(10) **Patent No.:** **US D627,632 S**
(45) **Date of Patent:** **** Nov. 23, 2010**

(54) **LOCKING MECHANISM FOR SECURING CORDS, HOSES OR CABLES**

(76) Inventors: **Warren Elmer**, 1383 Coast Meridian Road, Port Coquitlam, BC (CA) V3C 6L1; **Malcolm Kehr**, 179 Bracewell Drive, Penticton, BC (CA) V2A 6X1

(**) Term: **14 Years**

(21) Appl. No.: **29/345,362**

(22) Filed: **Oct. 14, 2009**

(30) **Foreign Application Priority Data**

Apr. 17, 2009 (CA) 130424

(51) **LOC (9) Cl.** **08-08**

(52) **U.S. Cl.** **D8/383**

(58) **Field of Classification Search** D8/330, D8/331, 333, 383; 70/14, 19, 202, 203
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,197,020	A *	9/1916	Farrar	70/203
3,667,259	A *	6/1972	Reque et al.	70/14
5,167,135	A *	12/1992	Gobeski	70/14
D334,883	S *	4/1993	Fraker et al.	D8/369
D477,768	S *	7/2003	Bridges et al.	D8/333
6,997,420	B2	2/2006	Yudis et al.		
D587,988	S *	3/2009	Johansson	D8/356
D613,137	S *	4/2010	Wieberdink et al.	D8/14

* cited by examiner

Primary Examiner—Holly H Baynham

Assistant Examiner—Sheryl Lane

(74) *Attorney, Agent, or Firm*—Procopio, Cory, Hargreaves & Savitch LLP

(57) **CLAIM**

The ornamental design for a locking mechanism for securing cords, hoses or cables, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a locking mechanism for securing cords, hoses or cables in a closed position, showing my new design;

FIG. 2 is a front view thereof;

FIG. 3 is a rear view thereof;

FIG. 4 is a left side elevation view thereof;

FIG. 5 is a right side elevation view thereof;

FIG. 6 is a bottom view thereof;

FIG. 7 is a top view thereof;

FIG. 8 is a perspective view thereof, illustrating the locking mechanism for securing cords, hoses or cables in an open position;

FIG. 9 is a perspective view of a second embodiment of the locking mechanism for securing cords, hoses and cables shown in FIG. 1.

FIG. 10 is a front view of the locking mechanism for securing cords, hoses or cables in the closed position;

FIG. 11 is a rear view of the locking mechanism for securing cords, hoses or cables in the closed position;

FIG. 12 is a left side elevation view of the locking mechanism for securing cords, hoses or cables in the closed position;


FIG. 13 is a right side elevation view of the locking mechanism for securing cords, hoses or cables in the closed position;

FIG. 14 is a bottom view of the locking mechanism for securing cords, hoses or cables in the closed position;

FIG. 15 is a top view of the locking mechanism for securing cords, hoses or cables in the closed position; and,

FIG. 16 is a perspective view of the locking mechanism for securing cords, hoses or cables in an open position.

1 Claim, 12 Drawing Sheets






FIGURE 1




FIGURE 2




FIGURE 3



FIGURE 4



FIGURE 5



FIGURE 6




FIGURE 7




FIGURE 8




FIGURE 9




FIGURE 10




FIGURE 11



FIGURE 12



FIGURE 13



FIGURE 14



FIGURE 15




FIGURE 16