



US00D627710S

(12) **United States Design Patent**
Rodicq et al.

(10) **Patent No.:** **US D627,710 S**
(45) **Date of Patent:** **** Nov. 23, 2010**

(54) **TIRE**

(75) Inventors: **Christophe Rodicq**,
Thionville-Veymerange (FR); **Murat**
Ahmet Yasar Susutoglu, Bissen (LU)

(73) Assignee: **The Goodyear Tire & Rubber**
Company, Akron, OH (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/364,888**

(22) Filed: **Jun. 30, 2010**

(51) **LOC (9) Cl.** **12-15**

(52) **U.S. Cl.** **D12/583**

(58) **Field of Classification Search** D12/546–550,
D12/568, 579–603, 900–901; 152/209.1,
152/209.8–209.19, 209.25–209.28

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D384,612 S	10/1997	Young et al.		D12/146
D385,234 S	10/1997	Young		D12/141
D448,709 S	10/2001	Le		D12/147
D454,535 S *	3/2002	Kemp, Jr.		D12/583
D457,855 S *	5/2002	Bawin et al.		D12/582
D458,215 S	6/2002	Le		D12/600
D458,580 S	6/2002	Young et al.		D12/512
D460,405 S *	7/2002	Schmidt		D12/583
D471,512 S *	3/2003	Weaver		D12/583
D472,202 S *	3/2003	Gillard		D12/583
D473,843 S	4/2003	Le et al.		D12/600
D480,045 S	9/2003	Durand et al.		D12/601
D497,875 S	11/2004	Le et al.		D12/594
D499,067 S *	11/2004	Wage		D12/583
D500,288 S	12/2004	Maziarka et al.		D12/601
D504,391 S	4/2005	Maziarka		D12/601
D504,865 S	5/2005	Maziarka et al.		D12/521
D517,468 S	3/2006	Le et al.		D12/566
D528,500 S	9/2006	Le et al.		D12/600
D533,498 S	12/2006	Scheuren et al.		D12/588
D534,484 S *	1/2007	Feider et al.		D12/584

D534,858 S 1/2007 Le et al. D12/534

D554,055 S 10/2007 Beauguitte et al. D12/600

D569,334 S 5/2008 Mariarka et al. D12/600

D585,816 S * 2/2009 Campana D12/584

D601,085 S 9/2009 Janesh et al. D12/600

(Continued)

Primary Examiner—Stacia Cadmus

(74) *Attorney, Agent, or Firm*—Richard B. O’Planick

(57) **CLAIM**

The ornamental design for a tire, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;

FIG. 2 is a front elevational view thereof;

FIG. 3 is a right side elevational view thereof; the opposite side elevational view being identical thereto;


FIG. 4 is an enlarged fragmentary front elevational view thereof;

FIG. 5 is a perspective view of a second embodiment of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread and that the opposite side view is identical thereto; and,

FIG. 6 is a front elevational view of a second embodiment, it being understood that an enlarged fragmentary view thereof would be substantially identical to that shown in FIG. 4, with the exception of the inclusion of the sidewall in solid lines.

In the drawings, the broken lines showing of the sidewall, inner bead and the peripheral boundary between the tire tread and the sidewall in FIGS. 1 through 4 depict environmental subject matter and form no part of the claimed design.

1 Claim, 6 Drawing Sheets



US D627,710 S

Page 2

U.S. PATENT DOCUMENTS				D604,691 S *	11/2009	Gervais	D12/584
D602,853 S	10/2009	Nopper et al.	D12/600	D606,010 S *	12/2009	Martin et al.	D12/583
D604,228 S	*	11/2009	Le et al.	D619,083 S *	7/2010	Reim et al.	D12/583
D604,229 S	*	11/2009	Le et al.	* cited by examiner			




FIG-1




FIG-2




FIG-3




FIG-4




FIG-5




FIG-6