



US00D628695S

(12) **United States Design Patent**
Ruf

(10) **Patent No.:** **US D628,695 S**
(45) **Date of Patent:** **** Dec. 7, 2010**

(54) **LANCING DEVICE**

(75) Inventor: **Christopher John Ruf**, Marietta, GA
(US)

(73) Assignee: **Facet Technologies, LLC**, Kennesaw,
GA (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/364,910**

(22) Filed: **Jun. 30, 2010**

Related U.S. Application Data

(62) Division of application No. 29/340,120, filed on Jul.
14, 2009, now Pat. No. Des. 621,042.

(51) **LOC (9) Cl.** **24-02**

(52) **U.S. Cl.** **D24/146**

(58) **Field of Classification Search** D24/113,
D24/114, 130, 133, 146-147; 600/385, 573,
600/583; 606/167, 172, 181-185; 210/453
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,895,147	A	1/1990	Bodicky et al.
D342,573	S	12/1993	Cerola
5,318,584	A	6/1994	Lange et al.
5,464,418	A	11/1995	Schraga
5,554,166	A	9/1996	Lange et al.
5,613,978	A	3/1997	Harding
5,984,940	A	11/1999	Davis et al.
6,045,567	A	4/2000	Taylor et al.
D428,150	S	7/2000	Ruf et al.
6,168,606	B1	1/2001	Levin et al.
D444,557	S	7/2001	LeVaughn et al.
D447,566	S	9/2001	LeVaughn et al.
6,322,575	B1	11/2001	Schraga
6,451,040	B1	9/2002	Purcell
6,558,402	B1	5/2003	Chelak et al.
6,575,939	B1	6/2003	Brunel
D493,532	S	7/2004	LeVaughn et al.

7,105,006	B2	9/2006	Schraga
D530,424	S	10/2006	Manser et al.
D560,805	S	1/2008	Young et al.
7,322,998	B2	1/2008	Kuhr et al.
D586,465	S	2/2009	Faulkner et al.
D586,916	S	2/2009	Faulkner et al.
D605,290	S	12/2009	Ruf et al.

(Continued)

Primary Examiner—Freda S Nunn

(74) *Attorney, Agent, or Firm*—Gardner Groff Greenwald &
Villanueva, PC

(57) **CLAIM**

The ornamental design for a lancing device, substantially as
shown and described.

DESCRIPTION

FIG. 1 is perspective view of a lancing device according to a
first embodiment of the design.

FIG. 2 is first side view of the lancing device design of FIG. 1.

FIG. 3 is a second side view of the lancing device design of
FIG. 1.

FIG. 4 is a front view of the lancing device design of FIG. 1.


FIG. 5 is a rear view of the lancing device design of FIG. 1.

FIG. 6 is a top view of the lancing device design of FIG. 1;
and,

FIG. 7 is a bottom view of the lancing device design of FIG.
1.

Portions shown in broken lines are for illustrative purposes
only and form no part of the claimed design.

1 Claim, 4 Drawing Sheets



US D628,695 S

Page 2

U.S. PATENT DOCUMENTS

7,651,512 B2	1/2010	Chelak et al.	2004/0162573 A1	8/2004	Kheiri
D611,602 S	3/2010	Zollers	2005/0125017 A1	6/2005	Kudrna et al.
D612,051 S	3/2010	Ruf	2005/0125019 A1	6/2005	Kudrna et al.
D621,042 S *	8/2010	Ruf D24/146	2005/0159768 A1	7/2005	Boehm et al.
D621,044 S	8/2010	Trissel et al.	2005/0234492 A1	10/2005	Tsai et al.
D621,045 S	8/2010	Trissel et al.	2006/0100655 A1	5/2006	Leong et al.
2003/0212344 A1	11/2003	Yuzhakov et al.	2006/0100656 A1	5/2006	Olson et al.
2004/0039302 A1	2/2004	Kim	2007/0083222 A1	4/2007	Schraga
			2008/0058631 A1	3/2008	Draudt et al.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7