

US00D629744S

(12) **United States Design Patent**
Umstot et al.

(10) **Patent No.:** **US D629,744 S**
(45) **Date of Patent:** **** Dec. 28, 2010**

(54) **TIRE**
(75) Inventors: **Dale Edward Umstot**, Atwater, OH (US); **Delwyn Lovell Harvey**, North Canton, OH (US); **Ashley Amanda Strader**, Akron, OH (US); **John Kotanides, Jr.**, Canton, OH (US)

D512,370 S 12/2005 Pang D12/579
D516,013 S 2/2006 Miller et al. D12/579
D516,999 S 3/2006 Miller et al. D12/579
D517,000 S 3/2006 Allen et al. D12/579

(73) Assignee: **The Goodyear Tire & Rubber Company**, Akron, OH (US)

(Continued)

(**) Term: **14 Years**

Primary Examiner—Stacia Cadmus
(74) *Attorney, Agent, or Firm*—Richard B. O’Planick

(21) Appl. No.: **29/366,267**

(57) **CLAIM**

(22) Filed: **Jul. 22, 2010**

The ornamental design for a tire, as shown and described.

(51) **LOC (9) Cl.** **12-15**
(52) **U.S. Cl.** **D12/579**
(58) **Field of Classification Search** D12/536,
D12/539, 542, 544, 568, 571, 577–603, 900–901;
152/209.1, 209.8–209.19, 209.25–209.28
See application file for complete search history.

DESCRIPTION

(56) **References Cited**

U.S. PATENT DOCUMENTS

D325,012 S	3/1992	Covert et al.	D12/147
D326,075 S	5/1992	Covert et al.	D12/147
D397,655 S *	9/1998	Takada	D12/579
D421,583 S *	3/2000	Kemp, Jr.	D12/594
D429,479 S	8/2000	Fierro et al.	D12/147
D431,801 S	10/2000	Poling	D12/151
D437,266 S	2/2001	Poling et al.	D12/146
D444,426 S	7/2001	Marazzi et al.	D12/146
D447,447 S	9/2001	Guspodin et al.	D12/147
D449,258 S *	10/2001	Rayman	D12/579
D449,800 S *	10/2001	Fierro et al.	D12/579
D456,341 S *	4/2002	Warchol et al.	D12/577
D465,763 S	11/2002	Umstot et al.	D12/600
D481,005 S	10/2003	Umstot et al.	D12/600
D486,782 S *	2/2004	Fukunaga et al.	D12/579
D487,249 S *	3/2004	Okamoto	D12/594
D503,921 S *	4/2005	Yamaura	D12/600
D504,657 S	5/2005	Allen et al.	D12/579
D505,387 S *	5/2005	Nonaka	D12/600

FIG. 1 is a perspective view of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;

FIG. 2 is a front elevational view thereof;

FIG. 3 is a right side elevational view thereof; the opposite side elevational view being identical thereto;


FIG. 4 is an enlarged fragmentary front elevational view thereof;

FIG. 5 is a perspective view of a second embodiment of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread and that the opposite side view is identical thereto; and,

FIG. 6 is a front elevational view of a second embodiment, it being understood that an enlarged fragmentary view thereof would be substantially identical to that shown in FIG. 4, with the exception of the inclusion of the sidewall in solid lines.

In the drawings, the broken lines showing of the sidewall, inner bead and the peripheral boundary between the tire tread and the sidewall in FIGS. 1 through 4 depict environmental subject matter and form no part of the claimed design.

1 Claim, 6 Drawing Sheets



US D629,744 S

Page 2

U.S. PATENT DOCUMENTS

D520,939 S	5/2006	Allen et al.	D12/600	D558,664 S	1/2008	Herbeuval et al.	D12/579
D530,265 S	10/2006	Hutz et al.	D12/579	D567,749 S	4/2008	Brown et al.	D12/579
D531,571 S	* 11/2006	Suzuki	D12/579	D604,232 S *	11/2009	Gannon et al.	D12/600
				D609,165 S *	2/2010	Fujioka	D12/579

* cited by examiner




FIG-1




FIG-2




FIG-3




FIG-4




FIG-5




FIG-6