



US00D631739S

(12) **United States Design Patent**
Craig et al.(10) **Patent No.:** **US D631,739 S**
(45) **Date of Patent:** **** Feb. 1, 2011**(54) **COMBINED CLIP DEVICE AND SUPPORT
FOR ELONGATED MEMBERS**(74) *Attorney, Agent, or Firm*—Harness, Dickey & Pierce,
P.L.C.(75) Inventors: **Marc Craig**, Brighton, MI (US); **Kris Weger**, Plymouth, MI (US)(57) **CLAIM**(73) Assignee: **ZSI, Inc.**, Canton, MI (US)

The ornamental design for a combined clip device and support for elongated members, as shown and described.

(**) Term: **14 Years****DESCRIPTION**(21) Appl. No.: **29/336,746**

FIG. 1 is a front, bottom, right side perspective view of a first embodiment of the combined clip device and support for elongated members shown in the non-operative position;

(22) Filed: **May 8, 2009**

FIG. 2 is a top view of the combined clip device and support of FIG. 1;

(51) LOC (9) Cl. **08-08**

FIG. 3 is a front view of the combined clip device and support of FIG. 1;

(52) U.S. Cl. **D8/396**

FIG. 4 is a view from the right hand side of the combined clip device and support of FIG. 1;

(58) Field of Classification Search **D8/356,**
D8/371, 394–396; D19/65, 34; D24/128;
24/570, 128, 67.9, 66.13; 248/74.1, 74.2,
248/74.3, 73, 215, 227.1, 49, 300, 301, 316.7,
248/51, 489; D11/214, 215, 78.1; 116/237

FIG. 5 is a rear view of the combined clip device and support of FIG. 1;

See application file for complete search history.

FIG. 6 is a view from the left hand side of the combined clip device and support of FIG. 1;

(56) **References Cited**

FIG. 7 is a bottom plan view of the combined clip device and support of FIG. 1;

U.S. PATENT DOCUMENTS

- 4,614,321 A * 9/1986 Andre 248/74.2
5,765,787 A * 6/1998 de Beers et al. 248/73
D424,922 S 5/2000 Sherman D08/395
6,371,419 B1 * 4/2002 Ohnuki 248/74.2
6,554,232 B1 * 4/2003 Macris 248/71
6,641,093 B2 * 11/2003 Coudrais 248/73
6,969,832 B1 * 11/2005 Daughtry, Sr. 219/531
7,240,880 B2 * 7/2007 Benoit et al. 248/65
7,614,589 B2 * 11/2009 Kato 248/55
7,753,320 B2 * 7/2010 Geiger et al. 248/71
7,802,761 B2 * 9/2010 Volchko 248/55
2002/0011542 A1 * 1/2002 Winton, III 248/74.1
2004/0099773 A1 * 5/2004 Sono et al. 248/71
2004/0140406 A1 * 7/2004 Kanie 248/73
2008/0210830 A1 * 9/2008 Sedivy et al. 248/73

* cited by examiner

Primary Examiner—Celia A Murphy
Assistant Examiner—John Windmuller

FIG. 8 is a front view of the combined clip device and support of FIG. 1 shown in the operative position for supporting an elongated member;

FIG. 9 is a front, bottom, right side perspective view of a second embodiment of the combined clip device and support for elongated members shown in the non-operative position;
FIG. 10 is a top view of the combined clip device and support of FIG. 9;

FIG. 11 is a front view of the combined clip device and support of FIG. 9;

FIG. 12 is a view from the right hand side of the combined clip device and support of FIG. 9;

FIG. 13 is a rear view of the combined clip device and support of FIG. 9;

FIG. 14 is a view from the left hand side of the combined clip device and support of FIG. 9;

FIG. 15 is a bottom plan view of the combined clip device and support of FIG. 9;




FIG. 16 is a front view of the combined clip device and support of FIG. 9 shown in the operative position for supporting an elongated member;

FIG. 17 is a front, bottom, right side perspective view of a third embodiment of the combined clip device and support for elongated members shown in the non-operative position;

FIG. 18 is a top view of the combined clip device and support of FIG. 17;

FIG. 19 is a front view of the combined clip device and support of FIG. 17;

FIG. 20 is view from the right hand side of the combined clip device and support of FIG. 17;

FIG. 21 is a rear view of the combined clip device and support of FIG. 17;

FIG. 22 is a view from the left hand side of the combined clip device and support of FIG. 17;

FIG. 23 is a bottom plan view of the combined clip device and support of FIG. 17; and,

FIG. 24 is a front view of the combined clip device and support of FIG. 17 shown in the operative position for supporting an elongated member.

It will be understood that the broken lines shown in FIGS. 8, 16, and 24 illustrate structure associated with the present invention when in the operative position, i.e., the broken lines represent an elongated member in the form of a tube or pipe, but form no part of the present invention.

1 Claim, 6 Drawing Sheets




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23




Fig. 24