

US00D632093S

(12) **United States Design Patent**
Butcher

(10) **Patent No.:** **US D632,093 S**
(45) **Date of Patent:** **** Feb. 8, 2011**

(54) **IMAGE DISPLAY DEVICE**

(76) **Inventor:** **Gleeston Butcher**, 950 Briar Hill
Avenue, Toronto, ON (CA) M6B 1M2

(**) **Term:** **14 Years**

(21) **Appl. No.:** **29/296,823**

(22) **Filed:** **Oct. 29, 2007**

Related U.S. Application Data

(62) Division of application No. 29/254,910, filed on Mar.
1, 2006, now Pat. No. Des. 559,559.

(51) **LOC (9) Cl.** **06-04**

(52) **U.S. Cl.** **D6/309**

(58) **Field of Classification Search** D6/300–314,
D6/469, 466, 495; D10/2, 15, 40; D14/375,
D14/308; 40/700, 765, 735, 780, 760, 152,
40/152.1, 154–157, 711; D11/131, 164;
220/62.2

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,014,122	A	3/1977	Woods	
4,807,377	A *	2/1989	Stuckel	40/711
326,281	A	5/1992	Funazaki	
D386,446	S *	11/1997	Favish	D11/131
392,110	A	3/1998	Tsui	
D430,565	S *	9/2000	Crane et al.	D14/308
480,222	A1	10/2003	Lee	
D488,089	S *	4/2004	Sellers	D11/164
D495,271	S *	8/2004	Lai	D11/131
D570,245	S *	6/2008	McAbee	D11/164
D575,189	S *	8/2008	Fortin et al.	D11/131
2009/0272741	A1 *	11/2009	Tseng	220/62.2

* cited by examiner

Primary Examiner—Philip S Hyder

Assistant Examiner—Sydney R Buffalow

(74) *Attorney, Agent, or Firm*—Vidas, Arrett & Steinkraus,
P.A.

(57) **CLAIM**

The ornamental design for an image display device, as shown
and described.

DESCRIPTION

FIG. 1 is a perspective view of the upper portion of the image
display device, the base portion being omitted from the view;

FIG. 2 is a side view of the upper portion of the image display
device, the base portion being omitted from the view;

FIG. 3 is a top view of the upper portion of the image display
device, the base portion being omitted from the view;

FIG. 4 is a bottom view of the upper portion of the image
display device, the base portion being omitted from the view;

FIG. 5 is an exploded perspective view of the complete image
display device;

FIG. 6 is a perspective view of the complete image display
device;

FIG. 7 is an exploded view of the upper portion of the image
display device, the base portion being omitted from the view;

FIG. 8 is a front view of the backing portion of the image
display device, the body and the base being omitted from the
view;

FIG. 9 is a side view of the backing portion of the image
display device, the body and the base being omitted from the
view;

FIG. 10 is a rear view of the backing portion of the image
display device, the body and the base being omitted from the
view;

FIG. 11 is a front view of the body of the image display
device, the backing and the base being omitted from the view;

FIG. 12 is a side view of the body of the image display device,
the backing and the base being omitted from the view;

FIG. 13 is a rear view of the body of the image display device,
the backing and the base being omitted from the view;

FIG. 14 is a perspective view of the upper portion of a second
embodiment of the image display device, the base portion
being omitted from the view;

FIG. 15 is a side view of the upper portion of the second
embodiment of the image display device, the base portion
being omitted from the view;




FIG. 16 is a top view of the upper portion of the second embodiment of the image display device, the base portion being omitted from the view;

FIG. 17 is a bottom view of the upper portion of the second embodiment of the image display device, the base portion being omitted from the view;

FIG. 18 is an exploded perspective view of the complete second embodiment of the image display device;

FIG. 19 is a perspective view of the complete second embodiment of the image display device;

FIG. 20 is an exploded view of the upper portion of the image display device of FIGS. 14 and 19, the base portion being omitted from the view;

FIG. 21 is a front view of the backing portion of the image display device of FIGS. 14 and 19, the body and the base being omitted from the view;

FIG. 22 is a side view of the backing portion of the image display device of FIGS. 14 and 19, the body and the base being omitted from the view;

FIG. 23 is a rear view of the backing portion of the image display device of FIGS. 14 and 19, the body and the base being omitted from the view;

FIG. 24 is a front view of the body of the image display device of FIGS. 14 and 19, the backing and the base being omitted from the view;

FIG. 25 is a side view of the body of the image display device of FIGS. 14 and 19, the backing and the base being omitted from the view; and,

FIG. 26 is a rear view of the body of the image display device of FIGS. 14 and 19, the backing and the base being omitted from the view.

The broken lines illustrate environmental structure that forms no part of the claimed design.

The design is the shape and configuration of an image display device having a generally cylindrical body and an attachable backing portion.

1 Claim, 4 Drawing Sheets




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7




Figure 8



Figure 9




Figure 10




Figure 11




Figure 12




Figure 13




Figure 14




Figure 15




Figure 16




Figure 17




Figure 18




Figure 19




Figure 20




Figure 21




Figure 22




Figure 23




Figure 24




Figure 25




Figure 26