



US00D632404S

(12) **United States Design Patent**
Karpiloff

(10) **Patent No.:** **US D632,404 S**

(45) **Date of Patent:** **** Feb. 8, 2011**

(54) **TRANSPORT TUBE HOLDER ASSEMBLY WITH INTERNAL AND EXTERNAL RIBS**

D601,714 S * 10/2009 Lohn et al. D24/226

(75) Inventor: **Kenneth Karpiloff**, Mamaroneck, NY (US)

(73) Assignee: **Becton, Dickinson and Company**, Franklin Lakes, NJ (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/364,213**

(22) Filed: **Jun. 21, 2010**

Related U.S. Application Data

(62) Division of application No. 29/354,047, filed on Jan. 19, 2010.

(51) **LOC (9) Cl.** **24-02**

(52) **U.S. Cl.** **D24/230**

(58) **Field of Classification Search** D24/216, D24/222, 224, 226, 227, 229, 230; 422/63-64, 422/99-104, 250, 266, 297, 330, 476; 206/563, 206/446; 211/69, 71-72, 74, 71.01
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- D264,810 S * 6/1982 Voltmann D24/226
- D271,239 S * 11/1983 Lemieux et al. D24/230
- D337,165 S * 7/1993 Malinoff D24/227
- 5,487,872 A * 1/1996 Hafeman et al. 422/102
- D414,271 S * 9/1999 Mendoza D24/224
- D420,743 S * 2/2000 Monks D24/224
- 6,019,225 A * 2/2000 Kalmakis et al. 206/563
- D448,854 S * 10/2001 Kuiper et al. D24/230
- D461,554 S * 8/2002 Lafond et al. D24/230
- D466,219 S * 11/2002 Wynschek et al. D24/227
- 6,875,405 B1 * 4/2005 Mathus et al. 206/446
- D529,622 S * 10/2006 Hadjis et al. D24/229
- D533,948 S * 12/2006 Schaub et al. D24/229
- D556,339 S * 11/2007 Coulling et al. D24/230
- D574,505 S * 8/2008 Muller-Cohn et al. D24/216

OTHER PUBLICATIONS

- U.S. Appl. No. 29/364,224, filed Jun. 21, 2010, to Kenneth Karpiloff.
- U.S. Appl. No. 29/364,217, filed Jun. 21, 2010, to Kenneth Karpiloff.
- U.S. Appl. No. 29/354,047, filed Jan. 19, 2010, to Kenneth Karpiloff.
- U.S. Appl. No. 29/354,354, filed Jan. 19, 2010, to Kenneth Karpiloff.

* cited by examiner

Primary Examiner—T. Chase Nelson

Assistant Examiner—Mark Cavanna

(74) *Attorney, Agent, or Firm*—The Webb Law Firm

(57) **CLAIM**

The ornamental design for a transport tube holder assembly with internal and external ribs, as shown and described.

DESCRIPTION

FIG. 1 is a frontwardly directed perspective view of a transport tube holder assembly with internal and external ribs in accordance with an embodiment of the present invention.

FIG. 2 is a rearwardly directed perspective view of the transport tube holder assembly of FIG. 1 in accordance with an embodiment of the present invention.

FIG. 3 is a top view of the transport tube holder assembly of FIG. 1 in accordance with an embodiment of the present invention.

FIG. 4 is a left side view of the transport tube holder assembly of FIG. 1 in accordance with an embodiment of the present invention.

FIG. 5 is a rear view of the transport tube holder assembly of FIG. 1 in accordance with an embodiment of the present invention.

FIG. 6 is a front view of the transport tube holder assembly of FIG. 1 in accordance with an embodiment of the present invention.

FIG. 7 is a right side view of the transport tube holder assembly of FIG. 1 in accordance with an embodiment of the present invention.




FIG. 8 is a bottom view of the transport tube holder assembly of FIG. 1 in accordance with an embodiment of the present invention.

FIG. 9 is a cross-sectional view of the transport tube holder assembly of FIG. 1 taken along line 9—9 in accordance with an embodiment of the present invention.

FIG. 10 is a close-up sectional view of the cross-sectional view of FIG. 9 taken along section 10 in accordance with an embodiment of the present invention.

FIG. 11 is a frontwardly directed perspective view of a second embodiment of the transport tube holder assembly in which the design of the first embodiment is shown broken away in order to indicate that a specific width and number of elements

disposed between the claimed regions of the assembly form no part of the claimed design; and,

FIG. 12 is a frontwardly directed perspective view of a third embodiment of the transport tube holder assembly in which the design of the first embodiment is shown broken away in order to indicate that a specific length and number of elements disposed between the claimed regions of the assembly form no part of the claimed design.

The broken lines shown in FIGS. 1-2, 4-7, and 11-12 are provided for the purpose of showing environment only, and form no portion of the claimed design.

1 Claim, 9 Drawing Sheets




FIG. 1




FIG.2




FIG. 3




FIG. 4




FIG. 7




FIG. 5




FIG. 6




FIG. 8




FIG. 9




FIG. 10




FIG.11




FIG.12