



US00D636036S

(12) **United States Design Patent**  
**Rios**

(10) **Patent No.:** **US D636,036 S**  
(45) **Date of Patent:** **\*\* Apr. 12, 2011**

(54) **SUSPENSION TRAINER**

(76) Inventor: **Rick Rios**, San Jose, CA (US)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/361,719**

(22) Filed: **May 13, 2010**

(51) **LOC (9) Cl.** ..... **21-02**

(52) **U.S. Cl.** ..... **D21/662**

(58) **Field of Classification Search** ..... D21/662,  
D21/684, 692, 694, 698; 482/38, 74, 91,  
482/92, 105, 118, 121-125, 129, 131, 139,  
482/143, 148; D30/153; 119/770, 797; D12/133  
See application file for complete search history.

6,113,564	A *	9/2000	McGuire	.....	602/32
D437,623	S *	2/2001	Ormsby	.....	D21/662
D489,422	S *	5/2004	Feder	.....	D21/662
6,921,354	B1 *	7/2005	Shifferaw	.....	482/91
D509,329	S *	9/2005	Willner et al.	.....	D30/153
7,044,896	B2	5/2006	Hetrick		
7,090,622	B2	8/2006	Hetrick		
7,481,747	B2 *	1/2009	Lechleiter	.....	482/57
2005/0085350	A1 *	4/2005	Shen	.....	482/91
2007/0173382	A1 *	7/2007	Axelrod	.....	482/91
2007/0173383	A1 *	7/2007	Feigenbaum et al.	.....	482/91

\* cited by examiner

*Primary Examiner* — Susan E Krakower

(57) **CLAIM**

The ornamental design for a suspension trainer, as shown and described.

(56) **References Cited**


**U.S. PATENT DOCUMENTS**



554,636	A *	2/1896	Hulsmann	.....	482/124
605,237	A *	6/1898	Spink	.....	482/129
906,763	A *	12/1908	Winship	.....	482/91
4,121,827	A *	10/1978	Weider	.....	482/125
D256,821	S *	9/1980	Weider	.....	D21/692
5,209,712	A *	5/1993	Ferri	.....	482/91
D343,881	S *	2/1994	Wilson	.....	D21/662
D346,632	S *	5/1994	Castellanos	.....	D21/692
D374,518	S *	10/1996	McIntyre	.....	D30/153
D375,924	S *	11/1996	Kramer	.....	D12/168
D383,810	S *	9/1997	Wilkinson	.....	D21/662
D424,638	S *	5/2000	Urso	.....	D21/662

**DESCRIPTION**

FIG. 1 is a front elevational view of a suspension trainer, showing my new design;  
FIG. 2 is a left side elevational view of a suspension trainer;  
FIG. 3 is a front perspective view of a suspension trainer, with the handles shown from the front;  
FIG. 4 is a front perspective view of a suspension trainer, with the handles shown from the side; and,  
FIG. 5 is a front perspective view of a suspension trainer, with the handles shown from the top.

**1 Claim, 4 Drawing Sheets**








FIG. 3




FIG. 4




FIG. 5