



US00D636726S

(12) **United States Design Patent**  
**Hiramura**

(10) **Patent No.:** **US D636,726 S**  
(45) **Date of Patent:** **\*\* Apr. 26, 2011**

(54) **CHARGE DEVICE**

(75) Inventor: **Fumito Hiramura**, Kyoto (JP)

(73) Assignee: **Arkray, Inc.** (JP)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/368,270**

(22) Filed: **Aug. 20, 2010**

(30) **Foreign Application Priority Data**

Feb. 23, 2010 (JP) ..... D2010-004105

(51) **LOC (9) Cl.** ..... **13-02**

(52) **U.S. Cl.** ..... **D13/108**

(58) **Field of Classification Search** ..... D13/107–110,  
D13/118–119, 184, 199; D14/251, 253,  
D14/432, 434; 320/107–115  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

|              |         |                      |         |
|--------------|---------|----------------------|---------|
| D324,370 S * | 3/1992  | Lay et al. ....      | D13/108 |
| D350,545 S * | 9/1994  | Olkkola et al. ....  | D14/253 |
| D351,132 S * | 10/1994 | Brooks et al. ....   | D13/108 |
| D399,821 S * | 10/1998 | Tyneski et al. ....  | D13/118 |
| D408,418 S * | 4/1999  | Pescetto et al. .... | D14/253 |
| D428,597 S * | 7/2000  | Murata et al. ....   | D13/108 |
| D461,447 S * | 8/2002  | Nawrozki ....        | D13/107 |
| D471,547 S * | 3/2003  | Ruohonen ....        | D14/253 |
| D561,182 S * | 2/2008  | Jenkins et al. ....  | D14/253 |

|              |         |                   |         |
|--------------|---------|-------------------|---------|
| D571,721 S * | 6/2008  | Yang .....        | D13/107 |
| D576,546 S * | 9/2008  | Yang .....        | D13/107 |
| D592,593 S * | 5/2009  | Crawley .....     | D13/108 |
| D603,332 S * | 11/2009 | Heine et al. .... | D13/107 |

\* cited by examiner

*Primary Examiner* — Rosemary K Tarcza

(74) *Attorney, Agent, or Firm* — Studebaker & Brackett PC;  
Donald R. Studebaker

(57) **CLAIM**

The ornamental design for a charge device, as shown and described.

**DESCRIPTION**

FIG. 1 is a top frontal perspective view of the charge device; FIG. 2 is a top rear perspective view of the charge device; FIG. 3 is a bottom frontal perspective view of the charge device;

FIG. 4 is a top view of the charge device;

FIG. 5 is a bottom view of the charge device;

FIG. 6 is a front view of the charge device;

FIG. 7 is a rear view of the charge device;


FIG. 8 is a right side view of the charge device;

FIG. 9 is a left side view of the charge device; and,

FIG. 10 is a perspective view of the charge device in a use state.

The broken lines showing a measuring device and data reading device in FIG. 10 are for the purpose of illustrating unclaimed portions of the design and form no part of the claimed design.

**1 Claim, 6 Drawing Sheets**






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10