



US00D639519S

(12) **United States Design Patent**  
**Gomez**

(10) **Patent No.:** **US D639,519 S**  
(45) **Date of Patent:** **\*\* Jun. 7, 2011**

(54) **PORTABLE REFUSE BAG SUPPORTING DEVICE**

**DESCRIPTION**

(76) Inventor: **Mark Gomez**, Topeka, KS (US)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/366,074**

(22) Filed: **Jul. 19, 2010**

(51) **LOC (9) Cl.** ..... **09-09**

(52) **U.S. Cl.** ..... **D34/6**

(58) **Field of Classification Search** ..... D34/1,  
D34/5, 6; 248/95, 97, 99, 100, 101; 141/390  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,349,991	A *	10/1967	Kessler	383/120
3,427,040	A *	2/1969	Jenkins	280/652
4,457,483	A *	7/1984	Gagne	248/97
D302,885	S *	8/1989	Barbee	D34/6
4,890,652	A *	1/1990	Hoerner	141/10
D307,968	S *	5/1990	Neal	D34/1
4,955,496	A *	9/1990	Nelson	141/390
5,056,679	A *	10/1991	Lonczak	141/390
5,897,084	A *	4/1999	Judge	248/95
2008/0023595	A1 *	1/2008	Armaly, Jr.	248/97
2010/0237202	A1 *	9/2010	Minicozzi	248/97

\* cited by examiner

*Primary Examiner* — Cynthia E Ramirez

(74) *Attorney, Agent, or Firm* — Hovey Williams LLP

(57) **CLAIM**

The ornamental design for a portable refuse bag supporting device, as shown and described.

FIG. 1 is a perspective view of the outer surface of a portable refuse bag supporting device in an unassembled configuration;

FIG. 2 is a perspective view of the inner surface of the device in an unassembled configuration;

FIG. 3 is an elevation view of the outer surface of the device in an unassembled configuration;

FIG. 4 is a side elevation view of the right side of the device as oriented in FIG. 3;

FIG. 5 is an elevation view of the inner surface of the device in an unassembled configuration;

FIG. 6 is a side elevation view of the right side of the device as oriented in FIG. 5;

FIG. 7 is a top view of the device as oriented in FIG. 3;

FIG. 8 is a perspective view of the device in a storage configuration;

FIG. 9 is an alternate perspective view of the device in a storage configuration;

FIG. 10 is an elevation view of the device in a storage configuration;

FIG. 11 is top view of the device as oriented in FIG. 10;

FIG. 12 is a rear perspective view of the device in a small-diameter use configuration;

FIG. 13 is a front perspective view of the device in a small-diameter use configuration;

FIG. 14 is a top view of the device in a small-diameter use configuration;


FIG. 15 is a rear perspective view of the device in a large-diameter use configuration;

FIG. 16 is a front perspective view of the device in a large-diameter use configuration; and,

FIG. 17 is a top view of the device in a large-diameter use configuration.

The broken line showing in the figures is included for the purpose of illustrating environment and forms no part of the claimed design.

**1 Claim, 10 Drawing Sheets**






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5





FIG. 6

L






FIG. 12




FIG. 13






FIG. 14






FIG. 15



FIG. 16




FIG. 17