

US00D640966S

(12) **United States Design Patent**
Fontaine et al.

(10) **Patent No.:** **US D640,966 S**
(45) **Date of Patent:** **** Jul. 5, 2011**

(54) **TIRE**

(75) Inventors: **Sebastien Willy Fontaine**, Oberfeulen (LU); **Anne-France Gabrielle Jeanne-Marie Cambron**, Mersch (LU); **Alexander Ossipov**, Leuven (BE); **Jean Joseph Victor Collette**, Arlon (BE); **Claude Charles Jacoby**, Wesserbillig (LU); **Xavier Jean-Francois Beot**, Virton (BE); **Vincent van Goor**, Rippweiler (LU)

(73) Assignee: **The Goodyear Tire & Rubber Company**, Akron, OH (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/358,842**

(22) Filed: **Apr. 1, 2010**

(51) **LOC (9) Cl.** **12-15**

(52) **U.S. Cl.** **D12/563**

(58) **Field of Classification Search** D12/533,
D12/544–568, 599–603, 900–901;
152/209.1–209.28, 455

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D355,876 S	*	2/1995	Diensthuber		D12/563
D362,420 S		9/1995	Heinen et al.		D12/147
D379,787 S	*	6/1997	Maxwell et al.		D12/566
D387,312 S	*	12/1997	Himuro et al.		D12/563
D387,714 S		12/1997	Heinen		D12/147
D429,194 S		8/2000	Heinen et al.		D12/147
D429,478 S		8/2000	Heinen et al.		D12/147
D431,800 S		10/2000	Heinen et al.		D12/147
D441,696 S	*	5/2001	Fierro et al.		D12/563
D451,868 S	*	12/2001	Graas et al.		D12/560
D452,198 S		12/2001	Heinen et al.		D12/146
D504,106 S		4/2005	de Briey-Terlinden		D12/553
			et al.		D12/553
D504,866 S		5/2005	Collette et al.		D12/553
D526,956 S	*	8/2006	Welbes et al.		D12/553
D533,131 S		12/2006	Fontaine et al.		D12/588

D548,677 S	8/2007	Welbes et al.		D12/553
D548,678 S	8/2007	Welbes et al.		D12/553
D548,679 S	8/2007	de Briey-Terlinden		D12/553
D551,613 S	* 9/2007	Lo		D12/564
D556,670 S	12/2007	Fontaine et al.		D12/553
D575,726 S	8/2008	Fontaine et al.		D12/564
D579,861 S	11/2008	Haas et al.		D12/553
D579,864 S	11/2008	Haas et al.		D12/566
D589,874 S	4/2009	Fontaine et al.		D12/564
D591,221 S	4/2009	Fontaine et al.		D12/563
D591,672 S	5/2009	de Briey-Terlinden		D12/553
		et al.		D12/553
D592,588 S	5/2009	Heinen et al.		D12/564
D595,639 S	7/2009	de Briey-Terlinden		D12/553

(Continued)

Primary Examiner — Stacia Cadmus

(74) *Attorney, Agent, or Firm* — Richard B. O'Planick

(57) **CLAIM**

The ornamental design for a tire, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;

FIG. 2 is a front elevational view thereof;



FIG. 3 is a right side elevational view thereof; the other side being a mirror image thereof;

FIG. 4 is an enlarged fragmentary front elevational view thereof;

FIG. 5 is a perspective view of a second embodiment of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread and that the opposite side view is a mirror image thereof; and, FIG. 6 is a front elevational view of a second embodiment, it being understood that an enlarged fragmentary view thereof would be substantially identical to that shown in FIG. 4, with the exception of the inclusion of the sidewall in solid lines.

In the drawings, the broken lines showing of the sidewall, inner bead and the peripheral boundary between the tire tread and the sidewall in FIGS. 1 through 4 depict environmental subject matter and form no part of the claimed design.

1 Claim, 6 Drawing Sheets



US D640,966 S

Page 2

U.S. PATENT DOCUMENTS				D600,195 S	9/2009	Fontaine et al.	D12/564
D595,640 S	7/2009	de Briey-Terlinden	D12/564	D601,946 S	10/2009	Fontaine et al.	D12/553
D596,109 S	7/2009	de Briey-Terlinden	D12/553	D606,007 S	12/2009	Fontaine et al.	D12/564
D597,475 S	8/2009	Heinen et al.	D12/553	* cited by examiner			
D597,476 S	8/2009	de Briey-Terlinden	D12/553				




FIG-1




FIG-2




FIG-3




FIG-4




FIG-5




FIG-6