US00D642172S

(12) United States Design Patent

Akana et al.

(10) Patent No.: US D642,172 S
(45) Date of Patent: ** *Jul. 26, 2011

(54) **ELECTRONIC DEVICE**

(75) Inventors: **Jody Akana**, San Francisco, CA (US); **Bartley K. Andre**, Menlo Park, CA (US); **Jeremy Bataillou**, San Francisco, CA (US); **Daniel J. Coster**, San Francisco, CA (US); **Daniele De Iuliis**, San Francisco, CA (US); **Evans Hankey**, San Francisco, CA (US); **Richard P. Howarth**, San Francisco, CA (US); **Jonathan P. Ive**, San Francisco, CA (US); **Duncan Robert Kerr**, San Francisco, CA (US); **Shin Nishibori**, Portola Valley, CA (US); **Matthew Dean Rohrbach**, San Francisco, CA (US); **Peter Russell-Clarke**, San Francisco, CA (US); **Christopher J. Stringer**, Woodside, CA (US); **Eugene Antony Whang**, San Francisco, CA (US); **Rico Zorkendorfer**, San Francisco, CA (US)

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

(*) Notice: This patent is subject to a terminal disclaimer.

(**) Term: **14 Years**

(21) Appl. No.: **29/377,272**

(22) Filed: **Oct. 19, 2010**

(51) **LOC (9) Cl.** **14-02**
(52) **U.S. Cl.** **D14/318**
(58) **Field of Classification Search** ..... D14/315–327; D18/1, 2, 7, 11; 235/145 A, 145 R; 341/22, 341/23; 345/104, 156, 168, 169, 173; 361/679.08, 361/679.09, 679.11, 679.26, 679.27
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D425,874	S *	5/2000	Tanimura	D14/318
D431,821	S *	10/2000	Mizuno	D14/318
D463,797	S *	10/2002	Andre et al.	D14/327
6,657,854	B2 *	12/2003	Horii et al.	361/679.09
6,744,623	B2 *	6/2004	Numano et al.	361/679.27
D501,472	S	2/2005	Kumano	
D501,660	S	2/2005	Kumano	
7,035,665	B2 *	4/2006	Kido et al.	455/566
D558,753	S	1/2008	Andre et al.	
D574,378	S	8/2008	Andre et al.	
D600,688	S	9/2009	Andre et al.	
D604,289	S	11/2009	Andre et al.	
D604,290	S	11/2009	Andre et al.	
D604,292	S	11/2009	Andre et al.	
D604,293	S	11/2009	Andre et al.	
D604,294	S	11/2009	Andre et al.	
D606,988	S	12/2009	Andre et al.	
D606,989	S	12/2009	Andre et al.	
D607,450	S	1/2010	Morishita et al.	
D611,043	S	3/2010	Andre et al.	
D611,045	S	3/2010	Andre et al.	
D611,469	S	3/2010	Andre et al.	
D613,284	S	4/2010	Solomon et al.	
D616,880	S	6/2010	Andre et al.	
D616,881	S	6/2010	Andre et al.	
D621,825	S	8/2010	Andre et al.	
D623,645	S	9/2010	Andre et al.	
D625,717	S	10/2010	Andre et al.	

OTHER PUBLICATIONS

United States Patent Application No. 29/375,023, filed Sep. 16, 2010, entitled "Electronic Device".
U.S. Appl. No. 29/377,271, filed Oct. 19, 2010, entitled "Electronic Device".
Sony Vaio X505, available at least as early as May 8, 2005.
Olidata Altro, available at least as early as Jun. 1, 2009.

* cited by examiner

Primary Examiner — Freda Nunn
(74) *Attorney, Agent, or Firm* — SAIDMAN DesignLaw Group

(57) **CLAIM**

The ornamental design for an electronic device, as shown and described.





DESCRIPTION

FIG. **1** is a top, front perspective view of a first embodiment of an electronic device showing our new design;
FIG. **2** is a bottom, rear perspective view thereof;
FIG. **3** is a front view thereof;
FIG. **4** is rear view thereof;
FIG. **5** is a left side view thereof;
FIG. **6** is a right side view thereof;
FIG. **7** is a top view thereof;
FIG. **8** is a bottom view thereof;
FIG. **9** is an additional top, front perspective view thereof, with the electronic device shown in an open position;
FIG. **10** is an additional bottom, rear perspective view thereof, with the electronic device shown in an open position;
FIG. **11** is an additional front view thereof, with the electronic device shown in an open position;
FIG. **12** is an additional top view thereof, with the electronic device shown in an open position;
FIG. **13** is an additional left side view thereof, with the electronic device shown in an open position;
FIG. **14** is an additional right side view thereof, with the electronic device shown in an open position;
FIG. **15** is a top, front perspective view of a second embodiment thereof;
FIG. **16** is a bottom, rear perspective view thereof;
FIG. **17** is a front view thereof;
FIG. **18** is rear view thereof;
FIG. **19** is a left side view thereof;
FIG. **20** is a right side view thereof;
FIG. **21** is a top view thereof;
FIG. **22** is a bottom view thereof;
FIG. **23** is an additional top, front perspective view thereof, with the electronic device shown in an open position;
FIG. **24** is an additional bottom, rear perspective view thereof, with the electronic device shown in an open position;
FIG. **25** is an additional front view thereof, with the electronic device shown in an open position;
FIG. **26** is an additional top view thereof, with the electronic device shown in an open position;
FIG. **27** is an additional left side view thereof, with the electronic device shown in an open position;
FIG. **28** is an additional right side view thereof, with the electronic device shown in an open position;
FIG. **29** is a top, front perspective view of a third embodiment thereof;
FIG. **30** is a bottom, rear perspective view thereof;
FIG. **31** is a front view thereof;
FIG. **32** is rear view thereof;
FIG. **33** is a left side view thereof;
FIG. **34** is a right side view thereof;
FIG. **35** is a top view thereof;
FIG. **36** is a bottom view thereof;
FIG. **37** is an additional top, front perspective view thereof, with the electronic device shown in an open position;
FIG. **38** is an additional bottom, rear perspective view thereof, with the electronic device shown in an open position;
FIG. **39** is an additional front view thereof, with the electronic device shown in an open position;
FIG. **40** is an additional top view thereof, with the electronic device shown in an open position;
FIG. **41** is an additional left side view thereof, with the electronic device shown in an open position; and,
FIG. **42** is an additional right side view thereof, with the electronic device shown in an open position.

In FIGS. **29-42** certain portions of the design such as the hinge, and keys are black.

The broken lines are for the purpose of illustrating portions of the electronic device and form no part of the claimed design.

The relatively light gray shade lines on the surface portions indicate contour and not surface decoration.

The gray shading on a portion of the electronic device in FIGS. **29-42** represents a metallic surface.

1 Claim, 27 Drawing Sheets



Fig. 1



Fig. 2

Fig. 3



Fig. 4



Fig. 5



Fig. 6



Fig. 7



Fig. 8



Fig. 9

Fig. 10



Fig. 11



Fig. 12



Fig. 14

Fig. 13



Fig. 15



Fig. 16



Fig. 17



Fig. 18



Fig. 19



Fig. 20



Fig. 21



Fig. 22



Fig. 23



Fig. 24



Fig. 25



Fig. 26



Fig. 28

Fig. 27



Fig. 29



Fig. 30



Fig. 31



Fig. 32



Fig. 33



Fig. 34



Fig. 35



Fig. 36



Fig. 37



Fig. 38



Fig. 39



Fig. 40



Fig. 42

Fig. 41