

US00D644600S

(12) **United States Design Patent**
Nicolas et al.

(10) **Patent No.:** **US D644,600 S**
(45) **Date of Patent:** **** Sep. 6, 2011**

(54) **TIRE**

(75) Inventors: **Bernard Robert Nicolas**, Arlon (BE);
Nizar Toumni, Ettelbruck (LU)

(73) Assignee: **The Goodyear Tire & Rubber Company**, Akron, OH (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/375,949**

(22) Filed: **Sep. 30, 2010**

(51) **LOC (9) Cl.** **12-15**

(52) **U.S. Cl.** **D12/602; D12/900**

(58) **Field of Classification Search** D12/568–603,
D12/900–901, 564–567; 152/209.1–209.28,
152/455

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D384,609 S	10/1997	Gillard et al.		D12/146
D384,620 S	* 10/1997	Gillard et al.		D12/602
D397,651 S	* 9/1998	Schuster		D12/602
D405,740 S	2/1999	Heinen et al.		D12/147
D425,830 S	* 5/2000	Young		D12/602
D427,954 S	* 7/2000	De Coninck		D12/602
D432,960 S	* 10/2000	Feider et al.		D12/602
D445,070 S	* 7/2001	Schuster		D12/602
D478,862 S	* 8/2003	Gillard et al.		D12/602
D481,670 S	11/2003	Harden, Jr. et al.		D12/595
D481,992 S	11/2003	Harden, Jr. et al.		D12/595
D498,206 S	11/2004	Cazin-Bourguignon et al.		D12/588
D514,504 S	* 2/2006	Robert		D12/602
D517,472 S	* 3/2006	Allison		D12/602
D541,737 S	5/2007	Cazin-Bourguignon et al.		D12/600
D548,174 S	* 8/2007	Souchet		D12/602
D581,347 S	11/2008	Feider et al.		D12/523
D583,309 S	12/2008	Licht et al.		D12/588
D583,312 S	* 12/2008	Murphy et al.		D12/602

D588,528 S	3/2009	de Barsey		D12/588
D598,369 S	* 8/2009	Beha		D12/602
D598,370 S	* 8/2009	Beha		D12/602
D599,282 S	9/2009	Nicolaas et al.		D12/588
D609,169 S	2/2010	Feider		D12/588
D610,974 S	* 3/2010	Hagiwara		D12/602
D624,490 S	* 9/2010	Kaji		D12/602
D631,002 S	* 1/2011	Cazin-Bourguignon et al.		D12/602
D637,152 S	* 5/2011	Maus et al.		D12/602

* cited by examiner

Primary Examiner — Stacia Cadmus

(74) *Attorney, Agent, or Firm* — Richard B. O'Planick

(57) **CLAIM**

The ornamental design for a tire, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;

FIG. 2 is a front elevational view thereof;

FIG. 3 is a right side elevational view thereof; the opposite side elevational view being identical thereto;



FIG. 4 is an enlarged fragmentary front elevational view thereof;

FIG. 5 is a perspective view of a second embodiment of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread and that the opposite side view is identical thereto; and,

FIG. 6 is a front elevational view of a second embodiment, it being understood that an enlarged fragmentary view thereof would be substantially identical to that shown in FIG. 4, with the exception of the inclusion of the sidewall in solid lines.

In the drawings, the broken lines showing of the sidewall, inner bead and the peripheral boundary between the tire tread and the sidewall in FIGS. 1 through 4 depict environmental subject matter and form no part of the claimed design.

1 Claim, 6 Drawing Sheets






FIG-1




FIG-2




FIG-3




FIG-4




FIG-5




FIG-6