

US00D645334S

(12) **United States Design Patent**
Kanemitsu et al.

(10) **Patent No.:** **US D645,334 S**

(45) **Date of Patent:** **** Sep. 20, 2011**

(54) **PULLEY**

(75) Inventors: **Toshiaki Kanemitsu**, Akashi (JP);
Kazuyuki Oda, Akashi (JP)

(73) Assignee: **Kanemitsu Corporation**, Akashi-shi
(JP)

(**) Term: **14 Years**

(21) Appl. No.: **29/345,906**

(22) Filed: **Oct. 23, 2009**

(30) **Foreign Application Priority Data**

Apr. 27, 2009	(JP)	2009-009659
Apr. 27, 2009	(JP)	2009-009660
Apr. 27, 2009	(JP)	2009-009661
Jun. 16, 2009	(JP)	2009-013598
Jun. 16, 2009	(JP)	2009-013599

(51) **LOC (9) Cl.** **08-05**

(52) **U.S. Cl.** **D8/360**

(58) **Field of Classification Search** D8/327,
D8/323, 349, 356, 354, 360, 399, 382; 439/501;
320/111, 114; 191/12.4; D15/148, 5, 146,
D15/147, 149; D11/26, 39; D23/269; D12/501,
D12/175, 204, 207, 208; 474/8, 29, 31, 37,
474/39, 41, 47-57, 69, 113, 135, 166
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,627,572	A *	5/1927	Olinger et al.	254/390
4,093,185	A *	6/1978	Newell	254/295
D285,044	S *	8/1986	Mockett	D8/354
D297,707	S *	9/1988	Kanemitsu	D8/360
D308,013	S *	5/1990	Kanemitsu	D8/360
D347,378	S *	5/1994	Warner	D8/360
D436,023	S *	1/2001	Johnson	D8/360
D459,197	S *	6/2002	Hodjat	D8/360
6,575,536	B2 *	6/2003	Chen	301/35.623

(Continued)

Primary Examiner — Cynthia Underwood

(74) *Attorney, Agent, or Firm* — Rankin, Hill & Clark LLP

(57) **CLAIM**

The ornamental design for a pulley, as shown and described.

DESCRIPTION

FIG. 1 is a front, right side and top perspective view of a pulley in accordance with the first embodiment of our new design;

FIG. 2 is a front elevation view of the pulley in accordance with the first embodiment of our new design;

FIG. 3 is a rear elevation view of the pulley in accordance with the first embodiment of our new design;

FIG. 4 is a left side view of the pulley in accordance with the first embodiment of our new design, a right side view being a mirror image thereof;

FIG. 5 is a top plan view of the pulley in accordance with the first embodiment of our new design, a bottom plan view being a mirror image thereof;

FIG. 6 is a sectional view taken along a line 6-6 of FIG. 2 of the pulley in accordance with the first embodiment of our new design;

FIG. 7 is a front, right side and top perspective view of a pulley in accordance with a second embodiment of our new design;

FIG. 8 is a front elevation view of the pulley in accordance with the second embodiment of our new design;

FIG. 9 is a rear elevation view of the pulley in accordance with the second embodiment of our new design;



FIG. 10 is a left side view of the pulley in accordance with the second embodiment of our new design, a right side view being a mirror image thereof;

FIG. 11 is a top plan view of the pulley in accordance with the second embodiment of our new design, a bottom plan view being a mirror image thereof; and,

FIG. 12 is a sectional view taken along a line 12-12 of FIG. 8 of the pulley in accordance with the second embodiment of our new design.

The broken lines are included for illustrative purposes and form no part of the claimed design.

1 Claim, 4 Drawing Sheets



Page 2

U.S. PATENT DOCUMENTS				7,614,611	B1 *	11/2009	Walton et al.	254/393
D481,615	S *	11/2003	Hodjat et al.	D8/360	D621,240	S *	8/2010	Lutter et al.
6,669,135	B1 *	12/2003	Hartley	242/390.9	7,874,411	B2 *	1/2011	Roberts et al.
D548,059	S *	8/2007	Dyson	D8/360	2004/0145123	A1 *	7/2004	Hystad
D560,469	S *	1/2008	Bartol et al.	D8/349	2004/0178398	A1 *	9/2004	Miller et al.
D598,480	S *	8/2009	Kanemitsu	D15/148	* cited by examiner			

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 6




Fig. 5




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 12




Fig. 11

