

US00D647040S

(12) **United States Design Patent**
Mathonet et al.

(10) **Patent No.:** **US D647,040 S**
(45) **Date of Patent:** **** Oct. 18, 2011**

(54) **TIRE**

(75) Inventors: **Vincent Benoit Mathonet**, Habay la Neuve (BE); **Christophe Henri Joseph Schyns**, Rossart (BE); **Phuoc Thuan Le**, Attert (BE); **Czeslaw Andrzej Ratajewicz**, Luxembourg (LU)

(73) Assignee: **The Goodyear Tire & Rubber Company**, Akron, OH (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/392,773**

(22) Filed: **May 26, 2011**

(51) **LOC (9) Cl.** **12-15**

(52) **U.S. Cl.** **D12/588**

(58) **Field of Classification Search** D12/568–603,
D12/900–901, 551–556; 152/209.1–209.28,
152/455

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D370,439 S	6/1996	Feider et al.	D12/141
D371,756 S *	7/1996	Kishi et al.	D12/588
D394,034 S	5/1998	Feider et al.	D12/147
D448,707 S	10/2001	Maziarka et al.	D12/147
D451,860 S	12/2001	Schuster et al.	D12/147
D464,614 S *	10/2002	Irimiya	D12/588
D481,670 S	11/2003	Harden, Jr. et al.	D12/595
D481,992 S	11/2003	Harden, Jr. et al.	D12/595
D500,733 S *	1/2005	Himuro	D12/588
D506,180 S *	6/2005	Wage	D12/588
D536,663 S	2/2007	Heinen et al.	D12/603
D554,053 S	10/2007	Feider et al.	D12/588
D555,081 S	11/2007	Feider et al.	D12/588
D588,984 S *	3/2009	Lee	D12/588
D592,589 S	5/2009	Dixon et al.	D12/600

D601,950 S *	10/2009	Pressley et al.	D12/588
D604,229 S	11/2009	Le et al.	D12/582
D604,230 S *	11/2009	Brown et al.	D12/588
D609,169 S *	2/2010	Feider	D12/588
D609,170 S	2/2010	Feider et al.	D12/588
D612,326 S *	3/2010	Lo	D12/588
D635,916 S *	4/2011	Krier	D12/588
D637,143 S *	5/2011	Ohara	D12/588
D640,185 S *	6/2011	Scheuren et al.	D12/588

* cited by examiner

Primary Examiner — Stacia Cadmus

(74) *Attorney, Agent, or Firm* — Richard B. O'Planick

(57) **CLAIM**

The ornamental design for a tire, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;

FIG. 2 is a front elevational view thereof;



FIG. 3 is a right side elevational view thereof; the opposite side elevational view being identical thereto;

FIG. 4 is an enlarged fragmentary front elevational view thereof;

FIG. 5 is a perspective view of a second embodiment of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread and that the opposite side view is identical thereto; and, FIG. 6 is a front elevational view of a second embodiment, it being understood that an enlarged fragmentary view thereof would be substantially identical to that shown in FIG. 4, with the exception of the inclusion of the sidewall in solid lines.

In the drawings, the broken lines showing of the sidewall, inner bead and the peripheral boundary between the tire tread and the sidewall in FIGS. 1 through 4 depict environmental subject matter and form no part of the claimed design.

1 Claim, 6 Drawing Sheets






FIG-1




FIG-2




FIG-3




FIG-4




FIG-5




FIG-6