

US00D648236S

(12) **United States Design Patent**
Rodrig

(10) **Patent No.:** **US D648,236 S**
(45) **Date of Patent:** **** Nov. 8, 2011**

(54) **COMBINATION TIRE PRESSURE AND
TREAD DEPTH GAUGE**

(75) Inventor: **Steven Rodrig**, Hillsborough, NJ (US)

(73) Assignee: **Measurement Ltd.**, Grand Cayman
(KY)

(**) Term: **14 Years**

(21) Appl. No.: **29/367,712**

(22) Filed: **Aug. 12, 2010**

(51) **LOC (9) Cl.** **10-04**

(52) **U.S. Cl.** **D10/86**

(58) **Field of Classification Search** D10/86;
73/732, 744, 742, 717, 741, 146.3, 146.8
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | | |
|-----------|---|----------|-------------------|--------|
| 4,631,831 | A | 12/1986 | Bacher et al. | |
| 4,970,894 | A | 11/1990 | Huang | |
| D317,880 | S | 7/1991 | Meehan | |
| D366,846 | S | * 2/1996 | Handfield et al. | D10/86 |
| D390,140 | S | * 2/1998 | Germanton | D10/86 |
| D395,835 | S | * 7/1998 | Okuyama et al. | D10/85 |
| 5,883,306 | A | 3/1999 | Hwang | |
| 5,895,845 | A | 4/1999 | Burger | |
| D409,509 | S | 5/1999 | Petrucelli et al. | |
| D409,931 | S | 5/1999 | Petrucelli et al. | |
| 5,987,978 | A | 11/1999 | Whitehead | |
| D440,893 | S | 4/2001 | Van Zeyl | |

(Continued)

Primary Examiner — Antoine D Davis

(74) *Attorney, Agent, or Firm* — Howard IP Law Group, PC

(57) **CLAIM**

The ornamental design for a combination tire pressure and tread depth gauge, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a combination tire pressure and tread depth gauge showing our new design, according to an embodiment of the invention;

FIG. 2 is a top view of the combination tire pressure and tread depth gauge of FIG. 1;

FIG. 3 is a right side elevational view of the combination tire pressure and tread depth gauge of FIG. 1;

FIG. 4 is a front elevational view of the combination tire pressure and tread depth gauge of FIG. 1;

FIG. 5 is a rear elevational view of the combination tire pressure and tread depth gauge of FIG. 1;

FIG. 6 is a left side elevational view of the combination tire pressure and tread depth gauge of FIG. 1;

FIG. 7 is a bottom view of the combination tire pressure and tread depth gauge of FIG. 1;

FIG. 8 is a perspective view of the combination tire pressure and tread depth gauge of FIG. 1, shown with a rod for measuring tread depth in an extended position;

FIG. 9 is a perspective view of a combination tire pressure and tread depth gauge, showing our new design, according to another embodiment of the invention, having the same right side elevational view, front elevational view, rear elevational view, left side elevational view and bottom view as set forth in FIGS. 3, 4, 5, 6 and 7, respectively;


FIG. 10 is a perspective view of a combination tire pressure and tread depth gauge, showing our new design, according to another embodiment of the invention, having the same right side elevational view, front elevational view, rear elevational view, left side elevational view and bottom view as set forth in FIGS. 3, 4, 5, 6 and 7, respectively;

FIG. 11 is a perspective view of a combination tire pressure and tread depth gauge, showing our new design, according to another embodiment of the invention, having the same right side elevational view, front elevational view, rear elevational view, left side elevational view and bottom view as set forth in FIGS. 3, 4, 5, 6 and 7, respectively; and,

FIG. 12 is a perspective view of a combination tire pressure and tread depth gauge, showing our new design, according to another embodiment of the invention, having the same right side elevational view, front elevational view, rear elevational view, left side elevational view and bottom view as set forth in FIGS. 3, 4, 5, 6 and 7, respectively.

The matter shown in dashed lines is environmental structure and forms no part of the claimed design.

1 Claim, 4 Drawing Sheets



| U.S. PATENT DOCUMENTS | | | | | | |
|-----------------------|----|---------|------------------|-----------|------|----------------------------------|
| D440,894 | S | 4/2001 | Van Zeyl | D526,229 | S | 8/2006 Stowers et al. |
| D440,895 | S | 4/2001 | Van Zeyl | D526,589 | S | 8/2006 Stowers et al. |
| D441,674 | S | 5/2001 | Van Zeyl | D526,922 | S | 8/2006 Stowers et al. |
| D447,970 | S | 9/2001 | Cappiello et al. | D534,092 | S | 12/2006 Kuskovsky |
| D450,257 | S | 11/2001 | Bressler et al. | D564,383 | S | 3/2008 Petrucelli et al. |
| D455,666 | S | 4/2002 | Cappiello et al. | D596,970 | S | 7/2009 Petrucelli |
| D459,257 | S | 6/2002 | Petrucelli | D603,733 | S | 11/2009 Stowers et al. |
| D459,668 | S | 7/2002 | Petrucelli | D606,435 | S * | 12/2009 Zheng D10/86 |
| D462,627 | S | 9/2002 | Petrucelli | D631,766 | S | 2/2011 Petrucelli |
| 6,634,223 | B2 | 10/2003 | Hartmann et al. | D631,768 | S | 2/2011 Petrucelli et al. |
| 7,010,969 | B1 | 3/2006 | Huang | 7,928,960 | B2 * | 4/2011 Baldo et al. 345/156 |
| D522,894 | S | 6/2006 | Stowers et al. | | | |

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4



Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12