



US00D648262S

(12) **United States Design Patent**
Hermann et al.

(10) **Patent No.:** **US D648,262 S**

(45) **Date of Patent:** **** Nov. 8, 2011**

(54) **TIRE**

(75) Inventors: **Robert John Hermann**, Cuyahoga Falls, OH (US); **John David Coots**, Wooster, OH (US); **Jonathan James Shondel**, Massillon, OH (US); **Daniel Scott Sheehan**, Akron, OH (US)

(73) Assignee: **The Goodyear Tire & Rubber Company**, Akron, OH (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/396,167**

(22) Filed: **Jun. 27, 2011**

(51) **LOC (9) Cl.** **12-15**

(52) **U.S. Cl.** **D12/579**

(58) **Field of Classification Search** D12/568-603, D12/900-901, 544; 152/209.1-209.28, 455
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D273,777 S	5/1984	Igarashi et al.	D12/147
D302,411 S	7/1989	Goergen et al.	D12/146
D302,412 S	7/1989	Goergen et al.	D12/146
D383,102 S	9/1997	Harris et al.	D12/147
D385,519 S	10/1997	de Briey-Terlinden et al.	D12/147
D385,520 S	10/1997	Scheuren et al.	D12/147
D388,033 S	12/1997	Scheuren et al.	D12/146
D410,420 S	6/1999	de Barsy	D12/147
D419,119 S	1/2000	Beauguitte et al.	D12/147
D444,109 S	6/2001	De Coninck et al.	D12/147
D457,489 S *	5/2002	Rayman	D12/579
D462,650 S *	9/2002	Rayman	D12/579
D471,151 S	3/2003	Otsuji	D12/559
D492,643 S	7/2004	Robert	D12/579
D517,977 S	3/2006	Robert	D12/579
D529,434 S *	10/2006	Regallis et al.	D12/579
D549,157 S	8/2007	Maus et al.	D12/544
D549,163 S	8/2007	Maus et al.	D12/579

D573,942 S *	7/2008	Song	D12/579
D577,657 S	9/2008	Maus et al.	D12/544
D586,731 S	2/2009	Neubauer et al.	D12/579
D586,735 S	2/2009	Lo	D12/602
D593,485 S *	6/2009	Davidson et al.	D12/579
D594,400 S *	6/2009	Pringiers	D12/579
D597,022 S *	7/2009	Pringiers	D12/579
D598,369 S	8/2009	Beha	D12/602
D598,370 S	8/2009	Beha	D12/602
D599,732 S	9/2009	Simon et al.	D12/580
D601,086 S	9/2009	Maus et al.	D12/602
D604,690 S	11/2009	Dixon et al.	D12/579

(Continued)

Primary Examiner — Stacia Cadmus

(74) Attorney, Agent, or Firm — Richard B. O’Planick

(57) **CLAIM**

The ornamental design for a tire, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;

FIG. 2 is a front elevational view thereof;

FIG. 3 is a right side elevational view thereof; the opposite side elevational view being identical thereto;


FIG. 4 is an enlarged fragmentary front elevational view thereof;

FIG. 5 is a perspective view of a second embodiment of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread and that the opposite side view is identical thereto; and,

FIG. 6 is a front elevational view of a second embodiment, it being understood that an enlarged fragmentary view thereof would be substantially identical to that shown in FIG. 4, with the exception of the inclusion of the sidewall in solid lines.

In the drawings, the broken lines showing of the sidewall, inner bead and the peripheral boundary between the tire tread and the sidewall in FIGS. 1 through 4 depict environmental subject matter and form no part of the claimed design.

1 Claim, 6 Drawing Sheets



US D648,262 S

Page 2

U.S. PATENT DOCUMENTS

D606,928 S *	12/2009	Song	D12/579	D620,428 S *	7/2010	Rayman	D12/579
D606,929 S *	12/2009	Song	D12/579	D629,744 S	12/2010	Umstot et al.	D12/579
D610,071 S *	2/2010	Song	D12/579	D631,002 S	1/2011	Cazin-bourguignon	
D610,074 S *	2/2010	Cerny	D12/579			et al.	D12/602
D612,800 S *	3/2010	Lundgren et al.	D12/579	D634,265 S *	3/2011	Shan et al.	D12/579
D614,118 S *	4/2010	Wells et al.	D12/579	D642,115 S *	7/2011	Pringiers	D12/579

* cited by examiner




FIG-1




FIG-2




FIG-3




FIG-4




FIG-5




FIG-6