



US00D648723S

(12) **United States Design Patent**
Harper et al.

(10) **Patent No.:** **US D648,723 S**

(45) **Date of Patent:** **** Nov. 15, 2011**

(54) **COORDINATE INPUT DEVICE**

(75) Inventors: **Pierre Harper**, Portland, OR (US);
Thomas Crisp, San Francisco, CA (US);
Felix Ballerstedt, Portland, OR (US)

(73) Assignee: **Wacom Co., Ltd.**, Saitama (JP)

(**) Term: **14 Years**

(21) Appl. No.: **29/366,122**

(22) Filed: **Jul. 20, 2010**

(30) **Foreign Application Priority Data**

Jan. 27, 2010 (JP) 2010-001782

(51) **LOC (9) Cl.** **14-02**

(52) **U.S. Cl.** **D14/390**

(58) **Field of Classification Search** D14/388-390,
D14/341, 383, 384, 374, 381, 356; D19/52;
D10/65; 178/18.01, 18.03-18.09, 18.11;
345/173-178

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D313,409 S *	1/1991	Chowdhree et al.	D14/389
D338,015 S *	8/1993	Mohri	D14/239
D362,662 S *	9/1995	Baudot	D14/389
D364,389 S *	11/1995	Shimizu	D14/389
D377,169 S *	1/1997	Chida	D14/389
D466,114 S *	11/2002	Nakata	D14/339
D486,149 S *	2/2004	Kawami et al.	D14/341
D487,742 S *	3/2004	Huang et al.	D14/341
D519,997 S *	5/2006	Hirota	D14/341
D525,621 S *	7/2006	Hirota	D14/346
D554,640 S *	11/2007	Ponnert et al.	D14/388
D556,199 S *	11/2007	Song	D14/357
D589,961 S *	4/2009	Hackenberg et al.	D14/388
D601,560 S *	10/2009	Matsumoto et al.	D14/346
D602,022 S *	10/2009	Heck et al.	D14/388
D625,726 S *	10/2010	Crisp et al.	D14/389

D625,727 S *	10/2010	Crisp et al.	D14/390
D625,728 S *	10/2010	Crisp et al.	D14/390
D627,779 S *	11/2010	Liao	D14/341
D629,400 S *	12/2010	Harper	D14/390
D629,401 S *	12/2010	Crisp et al.	D14/390
D629,402 S *	12/2010	Crisp et al.	D14/390
D629,798 S *	12/2010	Arie et al.	D14/341
D631,047 S *	1/2011	Hirota	D14/390
D631,880 S *	2/2011	Hirota	D14/383

FOREIGN PATENT DOCUMENTS

JP D1372732 11/2009

(Continued)

Primary Examiner — Melanie H Tung

Assistant Examiner — Deanna Fluegeman

(74) *Attorney, Agent, or Firm* — Seed IP Law Group PLLC

(57) **CLAIM**

The ornamental design for a coordinate input device, as shown and described.

DESCRIPTION

FIG. 1 is a front side elevational view of a coordinate input device showing my new design.

FIG. 2 is a rear side elevational view thereof.

FIG. 3 is a top plan view thereof.

FIG. 4 is a bottom plan view thereof.

FIG. 5 is a right side elevational view thereof.

FIG. 6 is a left side elevational view thereof.

FIG. 7 is a first perspective view thereof.


FIG. 8 is a second perspective view thereof.

FIG. 9 is the first perspective view thereof with a pen in broken lines held by a pen holder; and,

FIG. 10 is an enlarged perspective view of the pen holder as referenced in FIG. 9, shown separately for completeness of illustration.

The broken lines in the drawings illustrate the unclaimed environment of the coordinate input device and form no part of the claimed design.

1 Claim, 5 Drawing Sheets



US D648,723 S

Page 2

FOREIGN PATENT DOCUMENTS			
JP	D1372733 S	11/2009	JP D1372961 S 11/2009
JP	D1372784 S	11/2009	JP D1372962 S 11/2009
JP	D1372958 S	11/2009	JP D1378263 S 1/2010
JP	D1372960 S	11/2009	JP D1378527 S 1/2010

* cited by examiner



FIG. 1



FIG. 2




FIG. 3




FIG. 4



FIG. 5



FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10