



US00D651926S

(12) **United States Design Patent**
Akiyama et al.

(10) **Patent No.:** **US D651,926 S**
(45) **Date of Patent:** **** Jan. 10, 2012**

(54) **FIRE DETECTOR**

(75) Inventors: **Nobuyuki Akiyama**, Tokyo (JP);
Satoshi Yanagisawa, Tokyo (JP);
Masahito Ando, Tokyo (JP)

(73) Assignee: **Nittan Company, Limited**, Tokyo (JP)

(**) Term: **14 Years**

(21) Appl. No.: **29/387,984**

(22) Filed: **Mar. 22, 2011**

(30) **Foreign Application Priority Data**

Nov. 17, 2010 (JP) D2010-027653

(51) **LOC (9) Cl.** **10-05**

(52) **U.S. Cl.** **D10/106.5**

(58) **Field of Classification Search** D10/106.5,
D10/106.2, 121, 98, 81; 340/628, 632, 634,
340/544, 545, 555, 558, 571, 693.6; 493/333

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D435,800	S	*	1/2001	Higashi et al.	D10/106.5
D446,741	S	*	8/2001	Johnson et al.	D10/106.5
D450,008	S	*	11/2001	Sakurai et al.	D10/106.5
D485,200	S	*	1/2004	Berthold et al.	D10/106.5
D622,170	S	*	8/2010	Cargile	D10/106.5
D628,108	S	*	11/2010	Akdag et al.	D10/106.5

* cited by examiner

Primary Examiner — George D Kirschbaum

(74) *Attorney, Agent, or Firm* — Young & Thompson



(57) **CLAIM**

The ornamental design for a fire detector, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of the front, and bottom of a fire detector showing my (our) new design; FIG. 2 is a front view thereof; FIG. 3 is a rear view thereof; FIG. 4 is a top plan view thereof; FIG. 5 is a bottom plan view thereof; FIG. 6 is a right side view thereof; and, FIG. 7 is a left side view thereof. The broken lines disclosed in FIG. 3 depict environmental subject matter that forms no part of the claimed design.

1 Claim, 6 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7