



US00D653385S

(12) **United States Design Patent**
Parker et al.

(10) **Patent No.:** **US D653,385 S**
(45) **Date of Patent:** **** Jan. 31, 2012**

(54) **LIGHT CONDUCTIVE LIGHT EMITTER FOR LIGHT EMITTING DIODE LIGHT SOURCE**

(75) Inventors: **Jeffery R. Parker**, Richfield, OH (US);
Timothy M. Parker, Naples, FL (US)

(73) Assignee: **Rambus International Ltd.** (KY)

(**) Term: **14 Years**

(21) Appl. No.: **29/382,964**

(22) Filed: **Jan. 10, 2011**

(51) **LOC (9) Cl.** **26-99**

(52) **U.S. Cl.** **D26/118**

(58) **Field of Classification Search** D26/122,
D26/138, 118, 120, 76, 80, 63, 62, 68, 121,
D26/155, 152, 2, 24, 25, 26, 28, 46, 47, 49,
D26/60, 67, 71, 72, 73, 78, 79, 81, 83, 88,
D26/85, 93, 101, 102, 103, 104, 105, 110,
D26/113, 119, 123, 124, 128, 127, 129, 130,
D26/135, 137, 154, 59, 90, 140, 142, 145;
362/362, 363, 326, 329, 330, 342, 351, 356,
362/357, 296, 297, 299, 300, 301, 302, 317,
362/325, 377, 121, 147, 148, 151, 171, 186,
362/218, 219, 648, 650, 257, 279, 280, 290,
362/292, 293; D13/179, 180

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D286,682 S * 11/1986 Greenlee D26/63
D345,518 S * 3/1994 Merlo D10/106
D370,070 S * 5/1996 Kay D26/67
5,584,574 A * 12/1996 Haddad 362/359
D414,579 S * 9/1999 Denison et al. D26/68

D477,424 S * 7/2003 Avital D26/9
6,612,720 B1 * 9/2003 Beadle 362/287
6,874,905 B1 * 4/2005 Beadle 362/153.1
D519,662 S * 4/2006 Mullen D26/61
7,114,821 B2 * 10/2006 Currie et al. 362/96
D560,838 S * 1/2008 Monroe et al. D26/63
D583,975 S * 12/2008 Kushinskaya et al. D26/63
D596,342 S * 7/2009 Sabernig D26/105
D610,729 S * 2/2010 Kushinskaya et al. D26/63
2006/0193138 A1 * 8/2006 Montefusco 362/359

* cited by examiner

Primary Examiner — Kevin Rudzinski

(74) *Attorney, Agent, or Firm* — Renner, Otto, Boisselle & Sklar, LLP

(57) **CLAIM**

The ornamental design for a light conductive light emitter for a light emitting diode light source, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a light conductive light emitter for a light emitting diode light source showing our new design.

FIG. 2 is a front view thereof.

FIG. 3 is a back view thereof.


FIG. 4 is a side view of one side thereof, the opposite side being a mirror image.

FIG. 5 is a top view thereof; and,

FIG. 6 is a bottom view thereof.

The broken lines forming a curvilinear shape in FIG. 5 represent an internal boundary of the claimed design while all other broken lines are directed to environment structure of unclaimed portions of the light conductive light emitter; the broken lines form no part of the claimed design.

1 Claim, 2 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6