



US00D656430S

(12) **United States Design Patent**  
**Spater**

(10) **Patent No.:** **US D656,430 S**  
(45) **Date of Patent:** **\*\* Mar. 27, 2012**

- (54) **D-RING WITH SUPPORT BAR**
- (76) Inventor: **Christopher B Spater**, Portsmouth, NH (US)
- (\*\*) Term: **14 Years**
- (21) Appl. No.: **29/383,150**
- (22) Filed: **Jan. 13, 2011**
- (51) **LOC (9) Cl.** ..... **02-07**
- (52) **U.S. Cl.** ..... **D11/210; D11/218**
- (58) **Field of Classification Search** ..... D11/1-2, D11/200-201, 206-210, 214-218; 24/163 R, 24/169-171, 173, 177-179, 191, 194-195, 24/197, 200, 199, 129 B, 198, 307; D30/140; D2/625  
See application file for complete search history.

3,625,559 A *	12/1971	Lawrence	.....	294/74
D233,051 S	10/1974	Graigmyle		
D288,162 S *	2/1987	Hutton et al.	.....	D6/607
D322,234 S *	12/1991	Fildan	.....	D11/218
5,123,690 A	6/1992	Bailey		
D333,804 S	3/1993	Franklin		
D357,435 S	4/1995	Cook		
D358,567 S *	5/1995	Sirois	.....	D11/212
D364,126 S	11/1995	Ochiai		
D435,807 S	1/2001	Anscher		
6,467,573 B1 *	10/2002	Parker	.....	182/3
D621,296 S *	8/2010	Kennelty	.....	D11/212
D623,030 S	9/2010	Spater		
D625,654 S	10/2010	Spater		

\* cited by examiner

*Primary Examiner* — Ralf Seifert

(57) **CLAIM**  
The ornamental design for a D-ring with support bar, as shown and described.

(56) **References Cited**


**U.S. PATENT DOCUMENTS**


18,753 A *	12/1857	Lenzmann	.....	53/393
D21,114 S *	10/1891	Hoyt	.....	D11/212
D35,694 S	1/1902	Hull		
D56,042 S *	8/1920	Warner	.....	D11/212
1,602,305 A *	10/1926	Helm	.....	24/72.5
1,697,833 A	7/1928	Lane		
D94,087 S *	12/1934	Knoll	.....	D11/212
2,119,469 A *	5/1938	Kerngood	.....	24/200
D119,153 S *	2/1940	Bowder	.....	D11/200
D133,541 S *	8/1942	Kasen	.....	D11/212
D171,440 S *	2/1954	Chisholm	.....	D11/212
2,781,569 A *	2/1957	Eilertsen	.....	24/487
2,889,168 A *	6/1959	Engelhardt	.....	294/82.25
3,583,750 A *	6/1971	Norton	.....	294/74

**DESCRIPTION**


FIG. 1 shows a perspective view of my design for a D-ring with support bar;  
FIG. 2 is a front view thereof;  
FIG. 3 is a back view thereof;  
FIG. 4 is a top view thereof;  
FIG. 5 is a bottom view thereof;  
FIG. 6 is a side view thereof; and,  
FIG. 7 is another side view thereof.  
The D-ring with support bar of the present invention is designed to attach to one or more pieces of webbing.

**1 Claim, 2 Drawing Sheets**






**FIG. 1**



**FIG. 2**



**FIG. 3**



**FIG. 4**



**FIG. 5**



**FIG. 6**



**FIG. 7**