



US00D659084S

(12) **United States Design Patent**
Graas et al.

(10) **Patent No.:** **US D659,084 S**

(45) **Date of Patent:** **** May 8, 2012**

(54) **TIRE**

(75) Inventors: **Maurice Graas**, Reichlange (LU);
Richard Heinen, Habay-la-Neuve (BE);
Matthieu Pingonat, Fameck (FR);
Julien Alexandre Fursthos, Basse Ham
(FR); **Tony Raymond Gery Deroo**,
Hettange Grande (FR); **Christian**
Jean-Michel Jetten, Mabompre (BE);
Bernard Jean Francois Croissant,
Bastogne (BE); **Manfred Josef Jung**,
Freisen (DE); **Alexander Ossipov**,
Leuven (BE); **William Urbano**
Villamizar, Mersch (LU)

(73) Assignee: **The Goodyear Tire & Rubber**
Company, Akron, OH (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/401,088**

(22) Filed: **Sep. 7, 2011**

(51) **LOC (9) Cl.** **12-15**

(52) **U.S. Cl.** **D12/590**

(58) **Field of Classification Search** D12/551-556,
D12/568-603, 900-901; 152/209.1-209.28,
152/455

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D368,687 S	4/1996	Hayashi	D12/147
D384,923 S	* 10/1997	Allen et al.	D12/590
D392,226 S	3/1998	Howald et al.	D12/141
D432,956 S	10/2000	Ricquet	D12/141
D454,834 S	* 3/2002	Saito et al.	D12/590
D480,043 S	* 9/2003	Hiroko	D12/590
D490,045 S	5/2004	Delu et al.	D12/519
D515,019 S	2/2006	Umstot et al.	D12/519
D525,186 S	7/2006	Martin	D12/521
D531,116 S	10/2006	Heinen et al.	D12/590
D537,406 S	* 2/2007	Reim	D12/590

D542,217 S	5/2007	Heinen et al.	D12/555
D548,680 S	8/2007	Heinen et al.	D12/603
D560,595 S	1/2008	Bindner et al.	D12/521
D579,855 S	11/2008	Fontaine et al.	D12/521
D579,865 S	* 11/2008	Matsuyama et al.	D12/586
D586,726 S	2/2009	Baumard et al.	D12/521
D586,734 S	* 2/2009	Bindner et al.	D12/590
D593,931 S	6/2009	Fontaine et al.	D12/521
D606,926 S	12/2009	Heinen et al.	D12/521
D610,970 S	* 3/2010	You	D12/590
D613,235 S	4/2010	Kossi et al.	D12/521
D613,240 S	* 4/2010	Mukai	D12/590

(Continued)

Primary Examiner — Stacia Cadmus

(74) *Attorney, Agent, or Firm* — Richard B. O'Planick

(57) **CLAIM**

The ornamental design for a tire, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;

FIG. 2 is a front elevational view thereof;

FIG. 3 is a right side elevational view thereof; the opposite side elevational view being identical thereto;



FIG. 4 is an enlarged fragmentary front elevational view thereof;

FIG. 5 is a perspective view of a second embodiment of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread and that the opposite side view is identical thereto; and,

FIG. 6 is a front elevational view of a second embodiment, it being understood that an enlarged fragmentary view thereof would be substantially identical to that shown in FIG. 4, with the exception of the inclusion of the sidewall in solid lines.

In the drawings, the broken lines showing of the sidewall, inner bead and the peripheral boundary between the tire tread and the sidewall in FIGS. 1 through 4 depict environmental subject matter and form no part of the claimed design.

1 Claim, 6 Drawing Sheets



US D659,084 S

Page 2

U.S. PATENT DOCUMENTS

D628,952 S	12/2010	Villamizar et al.	D12/521	D639,719 S	6/2011	Harvey et al.	D12/521
D635,911 S	4/2011	Sieber et al.	D12/521	D639,720 S	6/2011	Harvey et al.	D12/521
D638,348 S	5/2011	Harvey et al.	D12/521	D646,626 S *	10/2011	Murata	D12/586

* cited by examiner




FIG-1




FIG-2




FIG-3




FIG-4




FIG-5




FIG-6