

US00D659515S

(12) **United States Design Patent**  
**Schoen et al.**

(10) **Patent No.:** **US D659,515 S**

(45) **Date of Patent:** **\*\* May 15, 2012**

(54) **ADJUSTABLE TIE DOWN DEVICE**

(76) Inventors: **Vulgens Schoen**, Washington, NJ (US);  
**Samuel M. Westwood, III**, Bethlehem,  
PA (US)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/368,811**

(22) Filed: **Aug. 30, 2010**

(51) **LOC (9) Cl.** ..... **08-05**

(52) **U.S. Cl.** ..... **D8/355; D8/367**

(58) **Field of Classification Search** ..... D8/37,  
D8/382, 354, 356, 363, 367, 355; 40/642.01;  
211/59.1, 70.6; 294/82.17, 82.19; 24/16 PB,  
24/68 CD, 68 R, 129 D, 376, 300, 301, 302;  
248/74.3, 220.41, 220.43, 222.12, 304, 289  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

1,519,854	A	12/1924	Lockwood	
2,539,997	A	1/1951	Graves	
3,525,128	A *	8/1970	Laszlo	24/16 PB
D289,698	S *	5/1987	Bates	D30/142
4,885,824	A	12/1989	Schwab	
5,402,557	A	4/1995	Dalen	
5,623,750	A	4/1997	Nasin	
6,049,950	A	4/2000	Cavallo	
D440,144	S *	4/2001	Todd	D8/354
D480,946	S *	10/2003	Estep, Jr.	D8/367
6,637,077	B2	10/2003	Doty	
D489,246	S *	5/2004	Bolieu	D8/367
6,755,383	B2 *	6/2004	Davis	248/508
6,851,163	B2	2/2005	Selby	
D525,861	S *	8/2006	Mackey et al.	D8/367
D537,708	S *	3/2007	Leung	D8/395
D551,541	S *	9/2007	Kuo	D8/367

D561,007	S *	2/2008	Kaesler	D8/354
7,343,648	B2	3/2008	Shaw	
D573,875	S *	7/2008	Anderson	D8/367
7,454,818	B1 *	11/2008	Backman, III	24/300
7,571,521	B1 *	8/2009	Backman, III	24/300
7,575,224	B1	8/2009	Madland	
D605,027	S *	12/2009	Leung	D8/367
D615,385	S *	5/2010	Arendt	D8/349
D624,391	S *	9/2010	Arendt et al.	D8/349
D639,356	S *	6/2011	Kassel	D21/662
D643,886	S *	8/2011	Kassel	D21/662
D644,700	S *	9/2011	Kassel	D21/662
D651,065	S *	12/2011	Gelmetti	D8/354
2006/0085956	A1	4/2006	Stevens	
2009/0223024	A1	9/2009	Bauer	
2010/0011543	A1 *	1/2010	Wang	24/300

\* cited by examiner

*Primary Examiner* — Mark Goodwin

(74) *Attorney, Agent, or Firm* — Doherty & Charney LLC

(57) **CLAIM**

The ornamental design for an adjustable tie down device, as shown and described.

**DESCRIPTION**

FIG. 1 is a perspective view of an adjustable tie down device, showing our new design;  
FIG. 2 is a top plan view thereof;  
FIG. 3 is a front view thereof;  
FIG. 4 is a left side view thereof;  
FIG. 5 is a right side view thereof;  
FIG. 6 is a rear view thereof; and,  
FIG. 7 is a bottom view thereof.

The broken line showing of a hook is included for the purpose of illustrating a portion of an adjustable tie down device and forms no part of the claimed design.

**1 Claim, 4 Drawing Sheets**




FIG. 1




FIG. 3

FIG. 2







FIG. 4




FIG. 5




FIG. 6




FIG. 7

