

US00D661809S

(12) **United States Design Patent**
Larsen

(10) **Patent No.:** **US D661,809 S**
(45) **Date of Patent:** **** Jun. 12, 2012**

(54) **ACOUSTIC COUPLER FOR A HEARING AID**

(75) Inventor: **Tina Ahlberg Larsen**, Birkerød (DK)

(73) Assignee: **Widex A/S**, Lyngø (DK)

(**) Term: **14 Years**

(21) Appl. No.: **29/365,677**

(22) Filed: **Jul. 13, 2010**

(30) **Foreign Application Priority Data**

Jan. 13, 2010 (EM) 001656281

(51) **LOC (9) Cl.** **24-99**

(52) **U.S. Cl.** **D24/174**

(58) **Field of Classification Search** D24/173-175,
D24/106; D14/205, 223, 224, 242, 249;
381/23.1, 312, 322-324, 328-330, 334; 181/129,
181/130, 135; 379/443, 444
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,845,838	A *	11/1974	Malmrose et al.	181/129
4,055,233	A *	10/1977	Huntress	181/135
D270,566	S *	9/1983	Bennett	D24/174
D399,001	S *	9/1998	Yabe et al.	D24/174
D444,237	S *	6/2001	Stone	D24/173
6,320,960	B1 *	11/2001	Lathrop et al.	379/430
6,398,717	B1 *	6/2002	Leysieffer et al.	600/25
D469,873	S *	2/2003	Warring et al.	D24/151
D577,432	S *	9/2008	Polselli et al.	D24/106
D589,151	S *	3/2009	Sabio	D24/174
2004/0071305	A1 *	4/2004	Frederiksen	381/312

* cited by examiner

Primary Examiner — Anhdao Doan

(74) *Attorney, Agent, or Firm* — Sughrue Mion, PLLC

(57) **CLAIM**

The ornamental design for a acoustic coupler for a hearing aid, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of an acoustic coupler according to a first embodiment;

FIG. 2 is a rear perspective view of the acoustic coupler of FIG. 1;

FIG. 3 is a side view of the acoustic coupler of FIG. 1; and

FIG. 4 is a rear view of the acoustic coupler of FIG. 1;

FIG. 5 is a side view of the acoustic coupler of FIG. 1, rotated ninety degrees about its axis relative to the side view of FIG. 3;

FIG. 6 is a front view of the acoustic coupler of FIG. 1;

FIG. 7 is a side view of the acoustic coupler of FIG. 1, rotated 90 degrees counterclockwise as viewed in FIG. 3;

FIG. 8 is a front perspective view of an acoustic coupler according to a second embodiment;

FIG. 9 is a rear perspective view of the acoustic coupler of FIG. 8;

FIG. 10 is a side view of the acoustic coupler of FIG. 8; and,



FIG. 11 is a rear view of the acoustic coupler of FIG. 8;

FIG. 12 is a side view of the acoustic coupler of FIG. 8, rotated ninety degrees about its axis relative to the view of FIG. 10;

FIG. 13 is a front view of the acoustic coupler of FIG. 8; and,

FIG. 14 is a side view of the acoustic coupler of FIG. 8, rotated 90 degrees counterclockwise as viewed in FIG. 10.

1 Claim, 14 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14