

US00D661842S

(12) **United States Design Patent**
Ibon et al.

(10) **Patent No.:** **US D661,842 S**
(45) **Date of Patent:** **** Jun. 12, 2012**

(54) **PAIRS OF BASEBALL BATTING GLOVES WITH PROTECTIVE SHOCK ABSORBING MEMBERS ON THE EXTERIOR OF EACH GLOVE WITH ONE PAIR TO BE WORN ON THE RIGHT HAND AND LEFT HAND OF A RIGHT HANDED BATTER AND ONE PAIR TO BE WORN ON THE LEFT AND RIGHT HAND OF A LEFT HANDED BATTER**

2008/0313785 A1* 12/2008 Rudd et al. 2/16
2009/0019613 A1* 1/2009 Carcaterra et al. 2/16
2009/0019618 A1* 1/2009 Winningham 2/161.1
2009/0044306 A1* 2/2009 Lamson et al. 2/16

* cited by examiner

Primary Examiner — Raphael Barkai
Assistant Examiner — Randall Gholson

(74) *Attorney, Agent, or Firm* — Thomas I. Rozsa

(75) Inventors: **James Ibon**, Porter Ranch, CA (US);
Steven J. Behrens, Costa Mesa, CA (US); **Jack A. Kasarjian**, Camarillo, CA (US); **Scott Boyer**, Valencia, CA (US)

(57) **CLAIM**

The ornamental design for pairs of baseball batting gloves with protective shock absorbing members on the exterior of each glove with one pair to be worn on the right hand and left hand of a right handed batter and one pair to be worn on the left and right hand of a left handed batter, as shown and described.

(73) Assignee: **XProTeX Sport Group Worldwide, LLC**, Camarillo, CA (US)

DESCRIPTION

(**) Term: **14 Years**

(21) Appl. No.: **29/314,839**

FIG. 1 is a top plan view of a first embodiment of the pairs of baseball batting gloves with protective shock absorbing members on the exterior of each glove with one pair to be worn on the right hand and left hand of a right handed batter and one pair to be worn on the left and right hand of a left handed batter which is a left handed glove used by a right handed batter, showing our design;

(22) Filed: **May 4, 2009**

(51) **LOC (9) Cl.** **29-02**

(52) **U.S. Cl.** **D29/115**

(58) **Field of Classification Search** D2/610,
D2/612, 614–623; D29/115, 116.3, 113,
D29/116.2, 117.1–119, 120.1, 123; 2/16,
2/159, 161.1–161.8, 162, 198, 170, 455,
2/908, 917; D24/190; D28/63; D32/40,
D32/42, 43, 41; D21/807; D3/215, 224,
D3/226, 218; 224/219, 222, 267, 237; 40/586,
40/633; 15/104.94, 107, 227; D4/134; D20/33
See application file for complete search history.

FIG. 2 is a bottom plan of the first embodiment;

FIG. 3 is a side elevational view when viewed from the right side of the first embodiment;

FIG. 4 is a side elevational view when viewed from the left side of the first embodiment;

FIG. 5 is a bottom end view of the first embodiment;

FIG. 6 is a top end view of the first embodiment;

FIG. 7 is a top plan view of a second embodiment of the pairs of baseball batting gloves with protective shock absorbing members on the exterior of each glove with one pair to be worn on the right hand and left hand of a right handed batter and one pair to be worn on the left and right hand of a left handed batter which is a right handed glove used by a right handed batter;

FIG. 8 is a bottom plan view of the second embodiment;

FIG. 9 is a side elevational view when viewed from the right side of the second embodiment;

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,700,405 A * 10/1987 Sternberg 2/161.1
2006/0206981 A1* 9/2006 Morrow et al. 2/161.1
2007/0226873 A1* 10/2007 Mattesky 2/159
2008/0083048 A1* 4/2008 Morrow et al. 2/16
2008/0120753 A1* 5/2008 Desjardins et al. 2/16
2008/0244797 A1* 10/2008 Winningham 2/16
2008/0244799 A1* 10/2008 Winningham 2/16
2008/0263747 A1* 10/2008 DeBlasis et al. 2/161.1




FIG. 10 is a side elevational view when viewed from the left side of the second embodiment;

FIG. 11 is a bottom end view of the second embodiment;

FIG. 12 is a top end view of the second embodiment;

FIG. 13 is a perspective view of the first and second embodiments of the present invention as worn by a right handed batter when gripping the bottom end of a baseball bat, the baseball bat is shown in dotted lines and is not a part of this invention and a portion of a batter's arm is also shown in dotted lines and is not a part of this invention;

FIG. 14 is a top plan view of a third embodiment of the baseball batting glove with protective shock absorbing members on the exterior of the glove which is a right hand glove used by a left handed batter, showing our design;

FIG. 15 is a bottom plan of the third embodiment;

FIG. 16 is a side elevational view when viewed from the right side of the third embodiment;

FIG. 17 is a side elevational view when viewed from the left side of the third embodiment;

FIG. 18 is a bottom end view of the third embodiment;

FIG. 19 is a top end view of the third embodiment;

FIG. 20 is a top plan view of a fourth embodiment of the pairs of baseball batting gloves with protective shock absorbing members on the exterior of each glove with one pair to be worn on the right hand and left hand of a right handed batter and one pair to be worn on the left and right hand of a left handed batter which is a left handed glove used by a left handed batter, showing our design;

FIG. 21 is a bottom plan of the fourth embodiment;

FIG. 22 is a side elevational view when viewed from the right side of the fourth embodiment;

FIG. 23 is a side elevational view when viewed from the left side of the fourth embodiment;

FIG. 24 is a bottom end view of the fourth embodiment;

FIG. 25 is a top end view of the fourth embodiment; and,

FIG. 26 is a perspective view of the third and fourth embodiments of the present invention as worn by a left handed batter when gripping the bottom end of a baseball bat, the baseball bat is shown in dotted lines and is not a part of this invention and a portion of a batter's arm is also shown in dotted lines and is not a part of this invention.

1 Claim, 26 Drawing Sheets




FIG 1




FIG-2




FIG-3




FIG-4




FIG-5




FIG-6




FIG-7




FIG-8




FIG-9




FIG-10




FIG-11




FIG-12




FIG-13




FIG 14




FIG-15




FIG-16




FIG-17




FIG-18




FIG-19




FIG-20




FIG-21



FIG-22




FIG-23




FIG-24




FIG-25




FIG-26