



US00D665509S

(12) **United States Design Patent**
Smith et al.

(10) **Patent No.:** **US D665,509 S**

(45) **Date of Patent:** **** Aug. 14, 2012**

(54) **STERILITY INDICATOR VIAL**

(75) Inventors: **Jeffrey D. Smith**, St. Croix, MN (US);
Jeffrey C. Pederson, Minneapolis, MN
(US); **Sailaja Chandrapati**, Woodbury,
MN (US)

(73) Assignee: **3M Innovative Properties Company**,
St. Paul, MN (US)

5,736,355 A	4/1998	Dyke	
5,750,184 A	5/1998	Imburgia	
5,872,004 A	2/1999	Bolsen	
5,928,935 A *	7/1999	Reuss et al.	435/288.1
5,955,296 A	9/1999	Roll	
5,968,807 A	10/1999	Kaiser	
6,025,189 A	2/2000	Bolea	
D445,908 S *	7/2001	Conway	D24/224
6,352,837 B1	3/2002	Witcher	

(Continued)

(**) **Term:** **14 Years**

(21) **Appl. No.:** **29/378,224**

(22) **Filed:** **Nov. 1, 2010**

(51) **LOC (9) Cl.** **24-01**

(52) **U.S. Cl.** **D24/224**

(58) **Field of Classification Search** D24/216,
D24/217, 219, 222-226, 231, 232, 169, 108,
D24/112, 117, 130; D10/81; 422/500, 547,
422/554; 435/287.1, 287.3, 287.4, 288.1,
435/288.3, 288.7, 31

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D222,352 S *	10/1971	Ferro	D24/224
3,814,522 A *	6/1974	Clark et al.	422/548
4,291,122 A	9/1981	Orelski	
4,461,837 A	7/1984	Karle	
4,528,187 A *	7/1985	Truglio	422/548
4,528,268 A	7/1985	Andersen	
4,591,566 A	5/1986	Smith	
4,732,850 A	3/1988	Brown	
4,885,253 A	12/1989	Kralovic	
5,167,923 A	12/1992	Van Iperen	
5,223,401 A	6/1993	Foltz	
5,242,370 A *	9/1993	Silver et al.	422/918
5,405,580 A	4/1995	Palmer	
5,482,171 A	1/1996	Palmer	
5,529,931 A	6/1996	Narayan	
5,552,320 A	9/1996	Smith	
D380,555 S *	7/1997	Kurosaki et al.	D24/224
D383,851 S *	9/1997	Wong	D24/224

FOREIGN PATENT DOCUMENTS

EP 0152298 8/1985
(Continued)

OTHER PUBLICATIONS

3M™ Attest™ 1292-S Biological Indicator for Steam 3M™ Attest™
Auto-Readers, Jan. 1, 2007, pp. 1-16.

Primary Examiner — Anhdao Doan

(74) *Attorney, Agent, or Firm* — Nicole J. Einerson


(57) **CLAIM**

The ornamental design for a sterility indicator vial, as shown
and described.

DESCRIPTION

FIG. 1 is a front perspective view of a sterility indicator vial,
of the new design;
FIG. 2 is a rear perspective view thereof;
FIG. 3 is a front elevational view thereof;
FIG. 4 is a rear elevational view thereof;
FIG. 5 is a right side elevational view thereof, the left side
elevational view being a mirror image of the right side eleva-
tional view;
FIG. 6 is a top plan view thereof; and,
FIG. 7 is a bottom plan view thereof.
The broken lines in the drawing views are included for the
purpose of illustrating portions of the sterility indicator vial
that form no part of the claimed design.

1 Claim, 2 Drawing Sheets



US D665,509 S

Page 2

U.S. PATENT DOCUMENTS

6,455,272 B1 * 9/2002 Gillis 435/31
D619,728 S * 7/2010 Bare et al. D24/224
D644,741 S * 9/2011 Sattler et al. D24/224
2003/0133830 A1 7/2003 Gonzalez
2005/0074833 A1 4/2005 Gillis
2008/0070272 A1 3/2008 Franciskovich

2008/0261296 A1 10/2008 Justi
2010/0075430 A1 * 3/2010 Hofstadler et al. 422/64

FOREIGN PATENT DOCUMENTS

WO 2010/045138 4/2010

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7