

US00D667325S

(12) **United States Design Patent**
Yamashita

(10) **Patent No.:** **US D667,325 S**

(45) **Date of Patent:** **** Sep. 18, 2012**

(54) **DISPLAY DEVICE WITH GRAPHICAL USER INTERFACE FOR COMBINED WEIGHING INSTRUMENT**

2009/0133939	A1 *	5/2009	Taylor et al.	177/108
2009/0277692	A1 *	11/2009	Tatsuoka et al.	177/25.18
2010/0000801	A1 *	1/2010	Smith et al.	177/25.15
2011/0036645	A1 *	2/2011	Kageyama et al.	177/25.18
2012/0031683	A1 *	2/2012	Schoen	177/25.12

* cited by examiner

(75) Inventor: **Kazuhiko Yamashita**, Akashi (JP)

(73) Assignee: **Yamato Scale Co., Ltd.**, Akashi-shi (JP)

Primary Examiner — Antoine D Davis

(**) Term: **14 Years**

(74) *Attorney, Agent, or Firm* — Alleman Hall McCoy Russell & Tuttle LLP

(21) Appl. No.: **29/390,902**

(57) **CLAIM**
The ornamental design for a display device with graphical user interface for a combined weighing instrument, as shown and described.

(22) Filed: **Apr. 29, 2011**

(30) **Foreign Application Priority Data**

DESCRIPTION

Oct. 30, 2010 (JP) 2010-026206

(51) **LOC (9) Cl.** **10-04**

(52) **U.S. Cl.** **D10/94; D10/49**

(58) **Field of Classification Search** D10/49,
D10/87, 88, 91, 94; 177/25.14, 25.13, 25.18,
177/210, 211, 239-243

See application file for complete search history.

FIG. 1 illustrates a first graphical state of a graphical user interface displayed on a display device associated with a combined weighing instrument; and,

FIG. 2 illustrates a second graphical state of the graphical user interface of FIG. 1.


The dashed lines of FIGS. 1 and 2 illustrate unclaimed graphical user interface elements. The dot-dashed lines in FIGS. 1 and 2 illustrate a display device for a combined weighing instrument, upon which a graphical user interface is displayed with the graphical states illustrated in FIGS. 1 and 2 for carrying out various operations of the combined weighing instrument. FIG. 2 shows a second graphical state caused by selecting a switching button in the first graphical state of FIG. 1, which causes the display to switch from the first graphical state shown in FIG. 1 to the second graphical state shown in FIG. 2, the second graphical state being an all function button display mode. The broken lines form no part of the claimed design.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,840,240	A *	6/1989	Toyoda et al.	177/25.18
D316,681	S *	5/1991	Takasuna et al.	D10/49
5,258,580	A *	11/1993	Bergholt	177/25.18
D421,399	S *	3/2000	Bennett et al.	D10/50
6,046,411	A *	4/2000	Kawanishi et al.	177/25.13
D460,010	S *	7/2002	Robinson	D10/91
6,830,476	B2 *	12/2004	Gesuita et al.	177/25.18
7,214,891	B1 *	5/2007	Hewitt et al.	177/25.15
D621,730	S *	8/2010	Driver et al.	D10/49
D630,114	S *	1/2011	Chupp	D10/91

1 Claim, 1 Drawing Sheet






FIG. 1




FIG. 2

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : D667,325 S
APPLICATION NO. : 29/390902
DATED : September 18, 2012
INVENTOR(S) : Kazuhiko Yamashita

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title Page;

In the Description of Fig. 1, at line 3, delete “; and” and insert a --.-- after ‘instrument’.

Signed and Sealed this
Twelfth Day of February, 2013



Teresa Stanek Rea
Acting Director of the United States Patent and Trademark Office